

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor to Secs 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original, Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
 A Y.Oak 15" dia. bears N.18¼°E., 601 lks.
 A Y.Oak 15" dia. bears N.5°W., 702 lks

James W. Byron, Deputy Co. Surveyor - Sept. 1, 1954
C.S. File ~~47/74~~ 46/74 (pg 26)

We found both original BTs alive and in good condition. The northwest tree is a B.Oak 3 ft. 6" dia. The northeast tree is a B.Oak, 5 ft. dia. Trees check for bearing and distance. Scribing visible and in good condition.
Set 1" I.P. with brass cap mkd. "County Surveyor's Office, ¼ S 14|13 1954, T26S R5W .
Scribed:
 8" W.Oak N.42°14'W., 95.2 ft. ¼ S 14 CS BT.
 20" B.Oak S.85°30'E., 243.1 ft. ¼ S 13 CS BT.

BLM Dependent resurvey by Timothy J. Moore, A. Bert Skeesick, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2065 surveyed May 2004/April 2005 - (DCSO records Vol. 57 Page(s) 22453-4)

The ¼ sec. cor. of secs. 13 and 14, perpetuated by Byron, in 1954, monumented with an iron pipe, 1¼" dia., firmly set, projecting 9" above the ground, with brass cap (properly) mkd from which the remains of original bearing trees
 A roothole bears N.18¼°E., 396.7 ft., with oak trunk alongside, 35" dia., with no marks visible on an opened blaze.
 An oak snag, 36" dia., bears N.5½°W., 462.9 ft., with scribe mark S visible on an opened blaze. (Record, N.5°W., 463.3 ft.)
and bearing trees mkd. by Byron
 An oak, 40" dia., bears S.85½°E., 242.6 ft., with a healed double blaze.
 An oak, 19" dia., bears N.42¼°W., 95.4 ft., with a healed double blaze.