

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set post cor. to Secs. 11, 12, 13, and 14, from which  
A Y.Oak 18" dia. bears S.13°E., 115 lks.  
A Y.Oak 12" dia. bears S.47°W., 72 lks.  
A W.Oak 16" dia. bears N.48°W., 42 lks.  
A W.Oak 14" dia. bears N.33°E., 24 lks.

James W. Byron, Deputy County Surveyor - September, 1954  
C.S. File 46/74 (pg 28-29) and R.M. 1-14

-----  
Corner renewed from original W.Oak BT, N.33°E., 15.8 ft.  
(now 18"). We cut out - center rotted but old face in fair  
condition. Some scribe marks visible - letter S visible.  
We also cut out 2 ft. W.Oak N.48°W., 27.7 ft. and find orig.  
blaze scribed 26S in good condition. Both trees alive and  
check for bearing and distance. We also found stump holes  
that check bearings & distances for orig. BTs, SW and SE.  
Set - A 1" x 36" I.P. with brass cap at corner point, mkd.  
County Surveyors Office T26S R5W 11|12 1954  
14|13

Blazed & scribed:

14" R.Fir, N.35°W., 75.0 ft. mkd. T26S R5W S11 CS BT.  
8" W.Oak N.37°E., 38.8 ft. mkd. T26S R5W S12 CS BT.  
8" W.Oak S.85°E., 9.8 ft. mkd. T26S R5W S13 CS BT.  
10" W.Oak S.86°W., 15.3 ft. mkd. T26S R5W S14 CS BT.

Douglas Co. Surveyors Office - Milo Godfrey & crew - 2/5/1964  
(added 6/30/2022) - C.S. File 49/125-31

-----  
BTs mkd in 1954 still in good condition.