

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853 (DCSO records Vol. 11 Page(s) 4479)

Set ¼ sec. post, from which
A W.Oak, 12" dia., bears S.62°W., 15 lks.
A Y.Oak, 24" dia., bears N.67°E., 80 lks.

LG Hicks - Field Book 129 pg 30 - Aug. 1914

3/4"x18" pipe
3" Oak post.
8" W.Oak N.48½°E., 11.5
10" W.Oak N.64°W., 32.3
18" W.Oak S.62°W., 9.9 (OBT)
30" B.Oak N.67°E., 55.0 (OBT)
Note: This information added 2/21/2003, DCSO.

Douglas Co. Surveyors Office - Milo Godfrey - Mar. 1964 -
C.S. File 49/125-69

Not found.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 2/5/2003 - C.S. File 66/58-4

Found - ¾" I.D. iron pipe fd flush with ground (1914) See
recently discovered Field book 4 - renumbered
#129 - pg. 30 for 1914 renewal.

1914 monument is good shape, corner falls in
pasture, BC/IP not set.

OBTs & 1914 renewal BTs now depressions in ground.
New - 30" dia., W.Oak double blazed & scribed "¼ S24 CS
BT" bears N.59°W., 92.0 ft.
11" dia., W.Oak double blazed & scribed "¼ S24 CS
BT" bears N.22°W., 76.1 ft.
29" dia., W.Oak single blazed & scribed "¼ S25 CS
BT" bears S.86°E., 98.3 ft.
38" dia., W.Oak double blazed & scribed "¼ S25 CS
BT" bears S.24½°W., 328.8 ft.

Compass decl. 17½°E.

Following positions are for location purposes only
NOT SURVEY GRADE

Equipment: Trimble GEOEXPLORER 3 System
File: R020600C
Point Name: T26SR5W SQ24

continued next page

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

	<u>1927</u>		<u>1983</u>
OCS	N 602361	E 1271781	N E
Latitude:	43°17'12.7"		Latitude:
Longitude:	123°14'08"		Longitude:
Offset to corner?	no		
Corrected for?			