

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853 -  
(DCSO Vol. 11 Page 4481)

-----  
Set 1/4 Sec. post, from which  
    A Y.Oak 14" dia., bears N.66°E., 58 lks.  
    A Y.Oak 18" dia., bears S.35°W., 28 lks.

-----  
Douglas Co. Surveyors Office - Milo Godfrey - Feb. 1964 -  
C.S. File 49/125

-----  
Not found.

-----  
BLM Dependent resurvey by Timothy J. Moore, A. Bert Skeesick,  
Cadastral Surveyors and Robert H. Browning, Survey Tech,  
under Group No. 2065 surveyed May 2004/April 2005 - (DCSO  
records Vol. 57 Page(s) 22451-2)

-----  
Point for the 1/4 sec. cor. of secs. 13 & 24, at proportionate,  
there is no remaining evidence of the original cor.  
Set a stainless steel post, 28" long, 2 1/2" dia., 21" in the  
ground, with brass cap mkd. T26S R5W

1/4    S 13  
       S 24  
       2004

from which

    A finned aluminum rod, 36" long, 3/4" dia., driven flush  
    with the ground for a reference monument, bears  
    S.11°28'57"E., 37.9 ft. with aluminum cap mkd. RM  
    T26SR5W 1/4 S24 37.9 FT. TO COR. 2004 and an arrow  
    pointing to the corner.

    A finned aluminum rod, 36" long, 3/4" dia., driven flush  
    with the ground for a reference monument, bears  
    N.60°27'15"W., 19.3 ft. with aluminum cap mkd. RM  
    T26SR5W 1/4 S13 19.3 FT. TO COR. 2004 and an arrow  
    pointing to the corner.

    Deposit a magnet in a white plastic case at the base of the  
    stainless steel post.