

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
 A Y.oak 15" dia. bears N.75°W., 24 lks.
 A Y.Oak 18" dia. bears S.33°W., 95 lks.

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; Mike Stone - Jan & Feb. 1964 - C.S. File 49/125-35

Found - 22" Oak N.75°W., 15.8 ft. (standing but dead) Cut open & find good scribing "S".
 Oak S.33°W., 62.7 ft. dead & down. Did not open.
Set - Brass cap at cor. mkd: County Surveyor's Office, 1964 T26S R5W ¼ S12 S13
New BTs - 15" D.Fir S.24°E., 14.3 ft. mkd. ¼ S13 CS BT.
 18" D.Fir N.13°W., 23.7 ft. mkd. ¼ S12 CS BT.

BLM Dependent resurvey by Timothy J. Moore, A. Bert Skeesick, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2065 surveyed May 2004/April 2005 - (DCSO records Vol. 57 Page(s) 22462-3)

The ¼ sec. cor. of secs. 12 and 13, perpetuated by Godfrey, in 1964, monumented with an iron pipe, 1¼" dia., firmly set, flush with the ground, with brass cap (properly) mkd. from which the remains of the remaining original bearing tree
 A roothole bears N.75°W., 15.8 ft., alongside of which is the oak trunk, 18" dia., with no marks visible.
and the remains of bearing trees mkd. by Godfrey
 A sawed fir stump, 18" dia., bears S.24¾°E., 14.0 ft., with a healed double blaze.
 A sawed fir stump, 21" dia., bears N.13°W., 23.4 ft., with a healed double blaze.
and new bearing trees
 A fir, 12" dia., bears N.55¾°E., 45.2 ft., mkd. ¼ S12 BT
 A double trunk madrone, 14" dia., bears S.76¾°W., 50.4 ft., mkd. ¼ S13 BT.