

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 36; & 31 of T26-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - James E. Freeman Contract #1 dated May 1851 (DCSO records, Volume 11 Page 4423 and 4426)</p> <p>-----</p> <p>Set ¼ sec. post on top of hill, from which A B.Oak 18" dia. bears N.76°E., 125 lks. A B.Oak 8" dia. bears S.9°W., 300 lks.</p>
<p>Approximately 1901, Volume 2 Page 266 By (?)</p> <p>-----</p> <p>Set pitch post 6" sq. for ¼ corner. Note: Both old bearing trees standing.</p>
<p>Douglas Co. Surveyors Office - Milo Godfrey - Mar. 1964 - C.S. File 49/125-71</p> <p>-----</p> <p>Not found. Did not find pine post. Area has been burned over possibly several times.</p>
<p>Robert Wade - For Dave Philippi, May 1, 1980 - M 83-72</p> <p>-----</p> <p>Set by proportionate measurement, 5/8" Iron Rod.</p>
<p>Douglas Co. Surveyors Office - Stephen Flause; Bill Stewart August 25, 1980 - C.S. 61/11-20</p> <p>-----</p> <p>Found - 5/8" I.R. protruding 2" from ground & a flagged stake mkd. "W ¼ Sec. 31". A thorough search for the orig. BTs reveals no evidence of these or the pitch post monument. A fenceline running randomly south & northeast lies 43 ft. due east of the 5/8" corner monument. Wade's map, M83-72 records the distance to the fence as 55 ft. This is apparently an error of measurement possible caused by not measuring on a true bearing & by the random coursing of the fenceline. No evidence of the monument having been located at 55 ft. is found.</p> <p>Set - The 5/8" x 30" iron rod found is referenced out, removed & replaced with a DCSO 2½" brass cap on a 1" x 30" I.P. The 5/8" I.R. is set on the east edge of the BC. Both monuments are firmly set & protrude 2" from the ground. Brass cap is mkd. "Douglas County Surveyor" T26S ¼ S36 R5W S31 R4W 1980.</p> <p>New BTs - A 16" DBH B.Oak bears N.46½°E., 40.9 ft. scribed "¼ S31 CS BT" on a double blaze. Cont.</p>

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 36; & 31 of T26-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 23" DBH approx. 50 ft. tall D.Fir snag bears
S.05°E., 90.3 ft. bark scribed BT near base.
A 21" DBH B.Oak bears N.18°W., 41.8 ft. scribed ¼
S36 CS BT on a double blaze.
No other suitable bearing objects available.
All accessories are marked with DCSO BT tags.