

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec Cor for 25 & 24; & 19, 30 of T26-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - James E. Freeman Contract #1 dated May 1851  
(DCSO records, Volume 11 Pages 4423 and 4425)

-----  
Set post cor. of secs. 19, 24, 25 and 30, from which  
Planted one quart of small stones, raised mound and  
made two pits, from which  
A B.Oak 18" dia. bears S.50°E., 214 lks. dist.

L.G. Hicks, for R.F. & Mae Lewis - "Plat G, Lewis Addn. to  
Sunshine Ranch" (now vacated) Vol. 5 Pg. 22, Oct. 14, 1914

-----  
3/4" x 18" Iron pipe cor. 19, 30, 24 and 25.

James W. Byron, Deputy - Milo Godfrey; Clete Putnam  
July 1960 - C.S. File 49/125-5

-----  
Found - 3/4" x 18" I.P. at corner as recorded by Hicks.  
No trace of orig. BT.  
Found corner is in N-S fence line which seems to  
line with Range line and as projected through  
1/4 corner S13|S18. Also corner location. Check  
call to foot of Hill, OK.

Fence line thus: (See sketch in CS File)  
Set - Brass cap at corner mkd. County Surveyors Office  
1960, R5W R4W

S 24 | S 19 T 26 S  
S 25 | S 30

New BTs - 10" B.Oak bears S.32°W., scribed S25 T26S R4W CS BT  
119.2 ft.

11" B.Oak bears N.72°E., 61.1 ft. scribed S19 T26S  
R4W CS BT.

11" B.Oak bears N.8°W., 18.1 ft. scribed S24 T26S  
R5W CS BT.

6" Oak bears S.7°E., 80.5 ft. scribed S30 CS BT.

Fd. Ok by Douglas Co. Surveyors Office - Randall W. Smith,  
Deputy - Stephen J. Flause - 2/5/2003 - C.S. File 66/58-4B

Fd. Ok by Neil Hibbs Feb. 2005 - 2005-0047 A&B