TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 13; & S.18 of T.26-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
A B.Oak, 12" dia. bears N.8°W., 320 lks. dist.
Made trench as per instructions.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; S.A. Bilow For Office Records - December 1958 - C.S. File 49/128-2 M 13-57

Found - Orig. 12" now 42" B.Oak N.7°48'W., 211.2 ft. I open and find good scribes "¼S".
Set brass cap at cor. mkd: ¼ S13|S18 T26S County Surveyor's
R5W R4W Office, 1958
New BTs - 12" W.Oak bears S.81°40'W. (true) 91.5 ft. scribed ¼ S13 CS BT.
9" W.Oak bears N.23°E., (true) 104.5 ft. scribed ¼ S18 CS BT.

BLM Dependent resurvey by Timothy J. Moore, A. Bert Skeesick, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2065 surveyed May 2004/April 2005 - (DCSO records Vol. 57 Page(s) 22451)

The ¼ sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., perpetuated by Byron, in 1958, monumented with an iron pipe, 1¼" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd.
from which the remains of the original bearing tree
An oak, 48" dia., bears N.8°W., 211.2 ft., with fragmentary scribe marks visible on a partially opened blaze.
and bearing trees mkd. by Byron
An oak, 14" dia., bears N.23¼°E., 104.7 ft., with a healed double blaze.
An oak, 18" dia., bears S.81½°W., 91.2 ft., with a healed double blaze.