

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 037010

PRIMARY CORNER DESCRIPTION SE Cor Churchill DLC #37

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Original - Addison R. Flint, Contract #28 dated April, 1854 ----- Set post, from which A W.Oak 35" dia. bears S.40°E., 162 lks. Raised mound with trench as per instructions.</p>
<p>B.B. Irving, Co. Surveyor For: Rollow Wilson Jan. 15, 1945 - C.S. File 38/5 - Vol. 4 Pg. 104 ----- Set a Sandstone 4 x 6 x 32". B.Oak S.57°E., 72.9 ft.</p>
<p>Milo E. Godfrey, Deputy Co. Surveyor - V.R. Tracy & Jack Barnett - August 1964 - C.S. file 52/87-92 ----- Found - Rock (4"x6" top) set by Irving, 1945. 40" B.Oak S.43°E. (Not S.57°E.) 72.9 ft. very plain scars visible. Cut cross in top of rock & scribed one new tree as follows: 25" Pine N.41°E., 157.4 ft. mkd. SE DLC 37 CS BT. Corner is in fence corner 14 ft. North of N. edge of concrete frame for cattle guard.</p>
<p>Found OK, May 1981 - M 88-1</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 7/10/2000 - C.S. File 66/16-20 ----- Found - 4"x6" top of stone w/chiseled "+" on top 1" below ground in E-W fence line 2½' east of fence cor. 40" now 43" dia., down B.Oak with healed blaze, root hole bears S.43°E., 72.9 ft. (1945) 25" now 30" dia., 2½" high pine stump with a fully healed lower blaze bears N.39¼°E., 157.4 ft. (rec. N.41°E., 157.4 ft.) 1964 NO OBT found. New - NW inside corner of concrete cattle guard box bears N.5½°E., 14.8 ft. 43" dia., B.Oak single blazed & scribed "SE DLC 37 CS BT" bears S.69°E., 132.0 ft. 31" dia., B.Oak single blazed & scribed "SE DLC 37 CS BT" bears N.89½°W., 228.0 ft. Set - A 5/8"x30" long IR with DCSO alum, cap stamped "SE DLC 37 2000" along southerly edge of found stone (south 0.3 ft) protrudes 6" above ground.</p>
<p>Fd. Ok by Carl Sweeden 8/2001, M 138-58 Fd. Ok by R. Quimby, 9/2008, 2008-0068A&B</p>