

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 038020

PRIMARY CORNER DESCRIPTION SSE Cor. Emmett DLC #38

Alias 062030 Description Int. L. Cor. Evans DLC #62
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #28 dated April, 1854

Set post, from which
 A B.Oak 20" dia. bears S.3°W., 45 lks.
 Raised mound with trench as per instructions.

Frank Cain, Co. Surveyor - Dec. 8, 1914 - Vol. 2 Pg. 267

Set sandstone 4" x 4" X 13" marked 38 on West and 62 on East side. A W.Oak 20" marked C.S. T26S R6W bears S.30°E., 60 lks.

Milo E. Godfrey, Deputy Co. Surveyor - V.R. Tracy; Jack Barnett - August 1964 - C.S. File 52/87-94

Found - 30" W.Oak S.30°E., 39.6 ft. opened several years ago scribing visible on edge of old face "8", most of face rotted away.
 Rock set by Cain, "x" on top.
Set - Brass cap at cor. mkd. County Surveyors Office 1964
 T26S R6W SE DLC 38 | DLC 62. Set along-side rock.
New BTs - 13" W.Oak N.18°W., 28.0 ft. mkd. SE DLC 38 CS BT.
 5" W.Oak S.82°W., 50.9 ft. mkd. DLC 62 CS BT.
Fence corner, fences NW & E SE, bears North 18' from corner.

Fd. Ok by Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 7/19/2000 - C.S. File 66/16-25

Found OK by C. Sweeden, Aug. 2001 - M138-58

Douglas Co. Surveyors Office - Stephen J. Flause - John A. Pike - June 10, 2004 - C.S. File 67/6-15

Found - From Cain's 1914 ren. a stone, the top surface of which is marked with an "X" & measures approx. 4x4" is set flush with the ground.
 Godfrey's 1964 a 2½" dia. brass cap, (properly) mkd, on a 1½" O.D. iron pipe set on northerly edge of fd. stone & protrudes 17" above ground with the protruding portion bent southerly to center. The brass cap over said stone.
 OBT. A large distinct roothole the approx. center of which bears S.3°W., 29.70 ft. (as per rec.)
 From Cain's 1914 ren. A W.Oak 20" now a 30" DBH W.Oak fallen on face the roothole of which bears S.28½°E., 39.6 ft. (rec. S.30°E., 39.6 ft.)
continued next page

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 038020

PRIMARY CORNER DESCRIPTION SSE Cor. Emmett DLC #38

Alias 062030 Description Int. L. Cor. Evans DLC #62
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

From Godfrey's 1964 ren. 2 then new BTs fd.
A 13" W.Oak now a double trunk W.Oak with a fully healed double blaze on the now 18" DBH easterly trunk. The center of the root crown of the double trunk bears N.17°W., 28.0 ft. (rec. N.18°W., 28.0')

A 5" W.Oak now 9" DBH W.Oak with a fully healed double blaze bears S.84°W., 50.9 ft., (rec. S.82°W., 50.0')

Previously noted fence corner is fd as described but E SE running fence is gone.

New - A 15" DBH B.Oak scribed "DLC 62 CS BT" on a double blaze bears N.65½°E., 84.5 ft.
A 37" DBH W.Oak scribed "DLC 62 CS BT" on a double blaze bears S.46°E., 69.2 ft.

Note - Monument is in sparse Oak woods on gentle north slope descending from Northerly edge of large WNW-ESE running field.

Fd. Ok by C. Sweeden, 9/2007 - M154-32