

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 043010

PRIMARY CORNER DESCRIPTION NE Cor. Evans DLC #43

Alias 849350 Description Meander Cor.
Alias 500344 Description M.C. East line Sec 22
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #28 dated April, 1854

Meander post on right bank of Umpqua River and NE Cor. C 43
from which:

- A Y.Oak 24" dia. bears N.15'E., 1.14 chs.
- A Y.Oak 26" dia. bears N.68¾°W., 2.38 chs.

F.C. Frear; Wit. Milton Miller; N.E. Richardson
Dec. 10, 1937 - C.S. 15/11

I reset as per old Y.Oak BT, cut down, N.¼°E., 75.2 ft. Marks
plain. Drove 1 x 36" I.Pipe from which

- A Maple 36" dia. bears N.70¼°W., 63.5 ft.
- A Maple 36" dia. bears S.82¾°W., 76.8 ft.

Ben B. Irving; Ray Irving; John Fee - County Surveyors office
December 20, 1954 - C.S. File 46/67

Found a 1" x 36" I.P. as set by Frear in Dec. 1937.
Found stumps of two 36" Maple BTs with scribing.
Set 1" I.P. with brass cap mkd. N E cor. D L C #43 1954
T 26 S, R 6 W, from which
A 9" Apple bears N.31¾°W., 22.0 ft.
No other trees available.

Milo E. Godfrey; Vernon Tracy; Mike Stone - Douglas Co.
Surveyors Office - July 30, 1962 - C.S. File 52/87-5

Reset Cap from reference hubs set August 15, 1961.
Corner falls at foot of fill on East side of County Road.
A ¾" Rod (R/W pin)-W. side of road-Eng. Sta. 131+79.93 -
P.C. bears N.53½°W., 67.5 ft.
A ¾" Rod (R/W pin)-W. side of road-Eng. Sta. 131+09.10 -
P.C. bears S.70½°W., 80.8 ft.
A ¾" Rod (R/W pin)-E. side of road-Eng. Sta. 131+09.12 -
P.T. bears S.1°W., 51.85 ft.

Fd. OK by K. DeGroot, May 2001 - LP 2001-0052