

PRIMARY CORNER DESCRIPTION SW Cor. T. Smith DLC #44

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #28 dated April, 1854

SW Cor. C 44 on right bank North Umpqua River, set post
from which,
 S B.Oak 8" dia. bears N.15°W., 24 lks.
 A B.Oak 12" dia. bears N.5°E., 200 lks.

N.E. Richardson, Deputy Co. Surveyor - Milo Godfrey;
L. Kershner, June 1946 - (No source reference found)

Reset from one OBT with scribe marks 24" Oak N.15°W., 15.8 ft.
and B.Oak stump N.5°E., 132.0 ft.
Remark OBT 24" B.Oak N.15°W., 15.7 ft.
W.Oak N.59½°E., 30.9 ft. mkd. SW - DLC #44 CS BT.
Set - 2" x 54" cast pipe, driven 8" underground on river
bank, approx. high water mark.

Milo E. Godfrey, Deputy - Wm. Stoffel; Mike Darby; Mike Stone
May, 1964 - C.S. File 52/87-12

Found - 2" pipe, buried 6" below ground surface.
 B.Oak, now 36" dia., N.15°W., 15.8 ft., scribing
 visible on badly rotted face "CS BT".
 No trace found of any other BTs.
New BTs - 10" W.Oak N.16½°E., 34.5 ft. mkd. SW DLC 44 CS BT.
 14" B.Oak N.78½°E., 71.3 ft. mkd. SW DLC 44 CS BT.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause -
2/26/2008 - C.S. File 67/25-17

Found - 2" I.D. iron pipe, buried 13" below ground surface.
 36" B.Oak, now down, center is rotted out, no scribe
 visible, root hole agrees well w/rec (N.15°W.,
 15.8 ft) OBT
 10" now triple trunk W.Oak, most westerly trunk
 shows fully healed double blaze is 15" dia.,
 center of root crown bears N.16½°E., 34.5 ft.
 (agrees w/rec) 1964 BT
 14" now 17" dia., B.Oak, fully healed double blaze
 bears N.77°E., 71.3 ft. (rec. N.78½°E., 71.3
 ft. 1964 BT
New - 25" dia., Ponderosa Pine double blazed & scribed "SW
 DLC 44 CS BT" bears N.36½°W., 137.5 ft.
Note - Corner lies about 15 ft. westerly of access rd. at
 Rod & Gun Club.
 Compass decl. 16¼°E.