

PRIMARY CORNER DESCRIPTION SW Cor. McKinney DLC #47

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original - Addison R. Flint, Contract #28 dated April, 1854 ----- Set post from which A Laurel 15" dia. bears S.88°W., 27 lks. dist. Raised mound with trench as per instructions.</p>
<p>H.L. Eppstein, Co. Surveyor - Wit: Chester Fisher; John Thennes - July, 1937 - C.S. File 15/6 - Vol. 4 Pg. 40 ----- Set ¾" x 4 ft. bolt sq. head from Charles Roberts old BT marked in 1905 (see record in Vol. 2 Pg. 136) Tree mkd. B.Oak. Marked C.S Cl. 4 (7 gone). BT for SW Cor. Cl. 47. I marked new BT as follows: Red Fir 8" dia. bears N.88°30'E., 42.2 ft. mkd. C.S. Cl. 47 B T.</p>
<p>Milo E. Godfrey, Deputy - Mike Stone - June 17, 1964 C.S. File 52/87-40 ----- Found - Bolt with square head set by Eppstein at cor. D.Fir now 20" N.88½°E., 42.2 ft. shows plain axe scar, did not open. Rotten remains of B.Oak S.50°W., 2.5 ft. This probably was tree mkd. by Roberts in 1905. 21" D.Fir S.79°E. 49.0 ft. with very plain axe blaze facing corner. Did not find any record of this tree. New BT - 14" Madrone S.33°E., 23.0 ft. mkd. SW DLC 47 CSBT.</p>
<p>Doug. Co. Surveyors Office - John Powell; J. Heritage October 6, 1972 - C.S. File 52/87-100 ----- Found - Bolt with square head at corner. 20" D.Fir N.88½°E., 42.2 ft. shows good scar (this tree will probably be cut) 14" Laurel now stob S.33°E. 23 ft. scribe visible BT New BTs - 22" W.Oak S.37°E., 27.3 ft. scribed SW DLC47 CS BT. 18" Triple Laurel N.39°E., 48.0 ft. scribed SW DLC 47 CS BT. Cor. lies on top of high bank of river approx. 150' S of house</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - John Pike - 12/04/2001 - C.S. File 66/29-27 ----- Found - ¾" bolt with a 1½" square nut on top protrudes 26" out of washed out portion of river high bank. (1937) continued next page</p>

PRIMARY CORNER DESCRIPTION SW Cor. McKinney DLC #47

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Corner is approx. 75 ft. SW along high bank from fence corner. (DLC corner is in danger of being lost if river floods)

8" now 34" dia., D.Fir with a fully healed single blaze bears East, 43.0 ft. (rec. N.88½°E., 42.2 ft.) (1937)

22" now 24" dia., W.Oak with a fully healed single blaze, bears S.35½°E., 28.2 ft. (Rec. S.37°E., 27.3 ft.) (1972)

18" triple trunk now 11" dia., Southerly trunked Madrone with a fully healed double blaze bears N.40½°E., 48.0 ft. to center of 11" trunk (rec. N.39°E., 48.0 ft.) (1972)

Set - A 5/8"x30" long iron rod with DCSO Alum. cap stamped "WC 10 FT EAST" East 10.0 ft. from bolt. Protrudes 1" out of ground.

Found BTs from Set 5/8" I.R.

34" dia., D.Fir East 33.0 ft.
11" dia., Madrone, N.30°E., 42.2 ft.
24" dia., W.Oak, S.15½°E. 23.8 ft.
Bolt West, 10 ft.