

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 047100

PRIMARY CORNER DESCRIPTION Interior L Cor McKinney DLC #47

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #28 dated April, 1854

-----  
To cor. at angle in east boundary of C 47.  
Set post in prairie, deposited stone 7 x 4. Raised mound  
with trench as per instructions.

Roberts - Sept. 8, 1905 - Field Book 9 Page 21 For: Adam  
Fisher.

-----  
Set S.E. L Cor of C1 47 in 26-6  
W.O. 8" S.20°W., 88 lks.  
W.O. 5" N.89°W., 40 lks.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy; Wm.  
Stoffel; M. Stone - July, 1964 - C.S. File 52/87-66

-----  
Found - 11" W.Oak S.20°W., 58.1 ft., has been opened  
previously, scribing visible "RP" & what  
appears to be "10".  
12" W.Oak N.89°W., 26.4 ft. prev. opened, portions  
of scribe marks visible on partly rotted face.  
Set - Brass cap at cor. mkd. County Surveyor's Office 1964  
T26S R6W Int. "L" DLC 47  
New Bts - 9" W.Oak N.88°W., 24.5 ft. mkd. Int. "L" DLC 47 CSBT  
9" W.Oak S.81°E., 22.2 ft. mkd. Int. "L" DLC 47 CSBT  
Corner is in fence corner. Fences E.-W. & S. This is a renewal  
of corner as set by Roberts in 1905.

Cor. fd. OK 2/26/79, K.Reed, DCSO, C.S. File 60/24-12  
Found OK, 7/90, MLP 1990-0066  
Fd Ok, 7/94, By Herman Pieske, 1994-0062 A-C  
Fd. Ok, 7/95, By D.Bentz, 1994-0094 A&B  
Fd. OK, 1/97, by D. Bentz, 1997-0021