

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 052040

PRIMARY CORNER DESCRIPTION SSW Cor. Clinkinbeard DLC #52

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>Original - Addison R. Flint, Contract #28 dated April, 1854 (DCSO DLC records Page 313)</p> <p>-----</p> <p>Set post, deposited stone 7x6 Raised mound with trench as per instructions.</p>
<p>Bert W Udell - For: Mar-Linn Timber Corp. - Dec. 1950 - M16-32</p> <p>-----</p> <p>Most southerly SW Cor. of Clinkerboard DLC. Found stone 2"x5" on top, firmly set in ground 1.5' W of corner post.</p>
<p>Douglas Co. Surveyors Office - Milo Godfrey - May 1964 - C.S. File 52/87-9</p> <p>-----</p> <p>Not Found. Fence Cor. only, fences north &amp; south.</p>
<p>Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 4/5/2007 - C.S. File 67/24-33</p> <p>-----</p> <p>Found - 2½" dia., brass cap, projects 2" above ground, mkd: T26S R6W DLC   DLC 46   <u>52</u> SSW COR 2006 PLS 1941</p> <p>Did not dig up sandstone as noted on DeGroot's map. Note: As of today, Nov. 1, 2007, DeGroot's map still not filed.</p> <p>No accessories noted on DeGroot's map.</p> <p>New - Ridge peak of feed barn roof at south end bears N.57°W., (no dist.) 5/8"x60" iron rod with 1½" dia., alum cap stamped "DOUGLAS CO. SURVEYOR BO 1 2007" bears S.38°E., 276.6 ft. (2½ ft. away from R/R R-O-W fence) 13" dia., Oregon Ash, double blazed &amp; scribed "SSW DLC 52 CS BT" bears S.37°W., 595.5 ft. 6 ft. dia., galv. culvert (goes under R/R tracks) bears S.17½°W., 453.6 ft.</p> <p>Note - Lies in open pasture approx. 300 NW (perpendicular) of R/R tracks. No fences nearby. Compass decl. 16¼°E.</p>
<p>continued next page</p>

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 052040

PRIMARY CORNER DESCRIPTION SSW Cor. Clinkinbeard DLC #52

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Kris DeGroot - For: Douglas County Inc. - March 2007 (Filed 3/16/2009 - added to record 8/2/2018) - M158-74

-----  
Found - 6"x4"x16" Sandstone with a 2"x5" top, buried 6" below ground and lying 1.5 ft West of a fence corner post broken off 6" below ground per M 16-32.

Set - I removed the original stone monument and in its exact position I set a 1½"(O.D.)x32" iron pipe, 32" in the ground with a 2½" brass cap stamped:

T26S R6W  
DLC | DLC  
46 | 52  
| SSW  
| COR  
2006

PLS 1941  
I buried the sandstone monument 0.3' North of BCIP & set a 5½' steel fence post 1.0 ft North of BCIP

Fd. BC 7/2018, R. Quimby, Vol 24 P1 (Back Nine Industrial Park)