

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 053050

PRIMARY CORNER DESCRIPTION SW Cor. Akin DLC #53

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Addison R. Flint, Contract #28 dated April, 1854 ----- Set post in prairie, deposited stone 7 x 5. Raised mound with trench as per instructions.</p>
<p>N.E. Richardson, D.C.S. -Milo Godfrey; Les Kershner May 13, 1946 - (No source reference found) (added 8/20/2024) - C.S. File 39/50 Pg 35 ----- 1¼" x 36" Shaft with 6" flange on top set at corner fence post. 8" W.Oak N.45°05'W., 137.7 ft. 12" W.Oak S.40°30'W., 80.3 ft.</p>
<p>Searched for - Not found July 1964, M.E.G. C.S. 52/87-77</p>
<p>Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 6/13/2007 - C.S. File 67/21-50 ----- Found - Axle not found, position falls in south bound pavement Interstate 5. ¾" I.Pipe at NW corner lot 19 of Mask Homesites (Vol. 6 Pg. 35) bears East 524.3 (rec.) 1946 5/8" I.Rod at SW corner of 3.43 ac parcel shown on M60-16, bears East 177.70 ft. (rec.) 1976 5/8" I.Rod at SE corner of 3.43 AC parcel shown on M60-16 bears East, 462.10 ft. (rec.) 1976 New - 5/8" dia., x 30" long iron rod w/alum cap 2" below surface at west edge of pavement. Cap mkd: DOUGLAS CO. SURVEYOR SW DLC 5 3 o 2007 Position was re-established by projecting rec. dist. 524.3 ft. West from a 1/2" IP at the NW cor. lot 19 Mask Homesites (Vol 6 Pg. 35). A 5/8" IR found at SE cor. lot 18 Mask Homesites was also found to inverse well with NW cor. lot 19 (meas. 465.12'; rec. 465.05') V. McLind's survey M.60-16 which maps position of DLC corner fit our bearings & distance very closely as well. 2½" dia., bronze DCS0 drill cap, set in slanted headwall of culvert stamped "B0 1 2007" bears S.30°W., 73.00 ft.</p> <p>continued next page</p>

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 053050

PRIMARY CORNER DESCRIPTION SW Cor. Akin DLC #53

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

5/8" dia., I.Rod set in concrete blob in I-5 R/W fence at Sta. 2345, 4x4 post alongside bears N.3¾°W., 271.9 ft. See St. Hwy map 7B-7-10.
21" dia., W.Oak, double blazed & scribed "SW DLC 53 CS BT" bears N.7°W., 140.0 ft.
5/8" dia., I.Rod in fence corner bears East 177.70 ft. See M60-16
Note - Corner falls in west edge of pavement on South bound I-5 approx. 180 ft. north of mile post 128 sign. Compass decl. 16¼°E.