

PRIMARY CORNER DESCRIPTION SE Corner Rayner DLC #61

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #28 dated April, 1954

-----  
Set post, from which

A B.Oak 20" dia. bears N.70°W., 48 lks.

Raised mound with trench as per instructions.

-----  
J.W. Cole, Deputy Co. Surveyor - May 1921 - F.B. 50 Pg. 61  
and M 1-69

-----  
I renewed this corner from the original BT which I chopped  
open & found the scribe marks. I set an iron pipe, also an  
Oak post 4 x 4 x 40".

-----  
Milo E. Godfrey, Deputy - Mike Stone - June 17, 1964  
C.S. File 52/87-35

-----  
Found - 1" I.P. in fence corner (fences West, North &  
approx. SE).

Rotten remnants of old Oak stump N.70°W., 31.7 ft.  
too far gone to find scribing or other marks.

13" W.Oak N.35°W., 28.8 ft. with upper & lower axe  
scars facing corner, mkd. by Boyer, according  
to Voytilla, but nor recorded.

New BTs - 13" W.Oak N.35°W., 28.8 ft. mkd. S.E. DLC 61 CS BT.

24" W.Oak S.87°W., 102.7 ft. mkd. SE DLC 61 CS BT.

-----  
Douglas County Surveyors Office - Randall Smith & Stephen  
Flause - May 7, 1997 - C.S. 64/74-28

-----  
Mon. Fd.- 1" I.D. iron pipe is found 2" below ground (1921)

Accessories Fd.-

13" now 18" dia. W.Oak, with a fully healed single  
blaze, bears N.35°W., 28.8' (agrees with rec.)  
1964

24" now 26" dia. W.Oak, with a fully healed single  
blaze, bears S.87°W., 102.7' (agrees with  
rec.) 1964

Evidence of a rotted oak stump, bears N.70°W., 31.7'  
(agrees with rec.) OBT

(Cont. Next Page)

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 061060

PRIMARY CORNER DESCRIPTION SE Corner Rayner DLC #61

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Mon. Set- Iron pipe is referenced and removed, measured 19" long. A 2 3/8" brass cap on a 1 3/8" O.D. by 32" long iron pipe is set at referenced position protrudes 1" above ground. 1" I.P. is set along north edge of BC/IP 3" under ground.

New Accessories -  
20" dia. Madrone, double blazed and scribed "SE DLC 61 CS BT", bears N.69°W, 44'.  
7" dia. Madrone, double blazed and scribed "SE DLC 61 CS BT", bears S.63½°E., 31.2'.

Corner lies at the projection of a north and west running fence line.

DCSO-GIS Corner visitation - 7/20/2004 - Typed: 1/25/2011 - C.S. File 67/33-1

-----  
Monument - BC/IP 1.25"  
Comment - ok