

PRIMARY CORNER DESCRIPTION Cor. Secs 7, 18; 12 & 13 T26-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to sec. 7,12,13, & 18, from which
A Y.Oak 10" dia. bears S.20°E., 54 lks.
A Y.Oak 14" dia. bears N.67½°E., 63 lks.
A Y.Oak 18" dia. bears N.54°W., 242 lks.
A Y.Oak 18" dia. bears S.83½°W., 134 lks.

Ben B. Irving - R.L. Irving; Paul Abeel; Epperly - For:
J.T. Epperly, July, 1926 - C.S. File 37/105, M 28-29

I found at this corner a rotten stake at a fence corner &
an original BT in good condition (which I did not chop open)
now a 16" B.Oak N.78½°E., 61 lks. Also, a B.Oak down and
rotting but with scribe marks in the stump still legible
S.79¾°W., 132 lks. From this evidence I set a 3" x 42" Oak
post , from which
A 16" B.Oak bears N.78°30'E., 39.4 ft. (old BT)
24" B.Oak bears N.23°18'W., 210 ft. mkd. S31 T26SR7W BT
14" B.Oak bears S.80°30'E., 59 ft. mkd S18 T26S R6W.
8" Fir bears S.40°50'W., 52 ft. mkd. S24 T26S R6W

Milo Godfrey, Deputy co. Surveyor - Vernon R.Tracy; Jack
Barnett - Aug. 1964 - C.S. File 52/87-96

Found - 20" D.Fir S.41°W., 52.0 ft. prev. opened, good
scribing visible.
27" B.Oak N.78½°E., 39.4 ft. shows fairly good scar
25" B.Oak S.80½°E., 59.0 ft. shows very plain scar.
32" B.Oak N.23¼°W., 210 ft. shows very good scar.
All trees, above, alive & in good condition.
Set - Brass cap at cor. mkd. County Surveyor's Office 1964
T26S S 12 | S 7
R7W S 13 | S 18 R6W
New BT - To replace tree 210.0 ft. from corner,
6" D.Fir N.15°W., 17.0 ft. mkd. S12 CS BT.
Corner is along NW side of old road or tail along foot of
hill

Doug. Co. Surveyors Office - Randall Smith; Stephen Flause
April 10, 1990 - C.S. File 64/9-2

Found - 1964 DCSO 2½" BC on a 1P" O.D. I.P. protruding 4"
above ground. BC/IP leans 0.4 ft. north of
plumb.
14" now 31" dia. B.Oak with a fully healed blaze
bears N.78½°E., 39.4 ft. (agrees w/rec) Orig.
(No other original BTs found)

continued next page
TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Cor Secs 7, 18; 12 & 13 T26-6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

8" now 23" dia. 1½ ft. tall D.Fir stump with a fully healed lower blaze bears S.41°W. 52.6 ft. (Rec. S.41°W., 52.0 ft.)
14" now 25" dia. B.Oak with a fully healed double blaze bears S.80½°E., 59.0 ft. (agrees w/rec)
24" now 35" dia. 2½ ft. tall Oak stump with a fully healed lower blaze bears N.23¼°W., 21.0 ft.
6" now 7" dia. 1½ ft. tall D.Fir stump with a fully healed lower blaze bears N.13¼°W., 17.0 ft. (Rec. N.15°W., 17.0 ft.)
New BTs- 8" dia. D.Fir double blazed & scribed "T26S R7W S12 CS BT" bears N.75¼°W., 15.9 ft.
11" dia. D.Fir double blazed & scribed "T26S R7W S13 CS BT" bears S.12½°W., 91.0 ft.
Corner lies at the intersection of a North and West running fence lines.

Fd OK, Glenn Baughman, November, 1991, M 114-24
Fd. Ok by D. Collier, Feb. 1996, 1996-0037
FD. OK by D. Edwards, Mar. 1997, M126-65