

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
(DCSO Records Gov't Vol. 11 Page 4572)

-----  
Set ¼ Sec. post, from which  
A Y.Oak 18" dia. bears N.34°E., 58 lks.  
A Y.Oak 15" dia. bears S.54¼°W., 52 lks.

Ben B. Irving - R.L. Irving; Paul Abeel; Epperly - For:  
J.T. Epperly, July, 1926 - C.S. File 37/105, M 28-29

-----  
After diligent search no traces of this corner were found  
although several line blazes were readily located. This cor-  
ner was relocated by proportional measurements between the  
section corners next East and West. A 2 x 36" I.Pipe was  
driven for the corner, from which  
A B.Oak 14" dia. bears N.22°E., 72.0 ft. mkd. S.7 T26S  
R.6 W. B.T.  
A Cedar 12" dia. bears S.66°W., 54.0 ft. mkd. S.18  
T.26S. R.6W. B.T.

Milo E. Godfrey, Deputy Surveyor - Wm. Stoffel; Mike Darby;  
Mike Stone - July 1964 - C.S. File 52/87-55

-----  
Found - Incense Cedar, now 30" dia. S.66°W., 54.0 ft. Shows  
very plain axe scars. Tree alive and in good  
condition.  
Hollow stub of B.Oak N.22°E., 72.0 ft. Found good  
reverse scribing  
Iron Pipe out of ground.  
Set - Brass cap mkd. "County Surveyor's Office 1964 T 26  
S R 6 W ¼ S 7 S 18." Reset I.P. alongside.  
New BT - 10" D.Fir N.60°E., 25.5 ft. mkd. ¼ S7 CS BT".  
Rescribe -30" I.Cedar S.66°W., 54.0 ft. mkd. "¼ S18 CS BT."

Fd. Ok by C. Sweeden, 9/2007 - M154-32