TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 & 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
A W.Oak 20" dia. bears N.60°W., 156 lks.
A W.Oak 16" dia. bears S.82°E., 182 lks.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey, Clete Putnam - Dec. 8, 1959 - C.S. File 52/5-2 - M 16-59

Found - Orig. 20" now 36" W.Oak N.60°W., 103.0 ft. I open and find good scribing "S".
No trace of orig. SE BT found.
Set - Brass cap at corner mkd: County Surveyor's ¼ S 6 / S 7 Office, 1959 T26S R6W
New BTs - 36" W.Oak N.60°W., 1-3.0 ft. (orig. BT) rescribed ¼ S6 CS BT.
10" W.Oak bears S.23½°W., 33.2 ft. scribed ¼ S 7 CS BT.
E. W. fence 15 ft. south of corner.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 7/19/2000 - C.S. File 66/16-25

Found - 1959 DCSO brass cap/iron pipe, protrudes 12" above ground.
10" now 13" dia., W.Oak with a fully healed double blaze, bears S.23½°W., 33.2 ft. 1959
20" now down 33" dia., rotted Oak roothole bears N.60°W., 103.0 ft. OBT
New - 8" dia., D.Fir single blazed & scribed "¼ S7 BT CS" bears S.53°W., 7.8 ft.
19" dia., B.Oak double blazed & scribed "¼ S7 CS BT" S.46°E., 42.3 ft.
11" dia., D.Fir double blazed & scribed "¼ S6 CS BT" bears N.55°E., 14.6 ft.

Fd. Ok by C. Sweeden, 9/2007 - M154-32