TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 5,6,7,8 from which
A Y.Oak 36" dia. bears S.73½°W., 580 lks.
A Y.Oak 36" dia. bears N.41¾°W., 382 lks.
A W.Oak 14" dia. bears N.60¼°E., 594 lks.
A W.Oak 24" dia. bears S.89°E., 295 lks.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; Clete Putnam - Dec.8, 1959 - C.S. 52/5-3 - M 16-59

Found - Orig. 36" now 60" B.Oak N.41¾°W., 252.1 ft. no scar shown, but checks bearing & distance.
Orig. 14" now 30" W.Oak N.60¼°E., 392 ft. I open & find good scribing "T".
Orig. 36" now 60" B.Oak down, (Rec. S.73½°W., 382.8) I find should be S.73½°W., 143.0 ft. I open & find good scribing "T26S".
Orig. SE BT not found.

Set - Brass cap at corner mkd:County Surveyors Office 1959

S 6	S 5
S 7	S 8

T26S R6W

New BTs - 11" B.Oak bears S.15½°W., 23.0 ft. scribed S 7 T26S R6W CS BT.
21" Laurel bears S.21½°E., 33.0 ft. scribed S 8 T26S R6W CS BT.
6" B.Oak bears N.32°E., 13.2 ft. scribed S 5 T26S R6W CS BT.
12" W.Oak bears N.32°W., 50.0 ft. scribed S 8 T26S R6W CS BT.

I find ½" Iron rod bears East 35.0 ft. May have been set for Section corner by State.

Fd. Ok by D. Edwards, 1/97, M 126-51.

Fd. Ok by Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 7/19/2000 - C.S. File 66/16-25

DCSO-GIS Corner visitation - 6/21/2004 - Typed: 1/25/2011 - C.S. File 67/33-1

Monument - BC/IP 1.25"
Comment - OK

Fd. Ok by C. Sweeden, 9/2007 - M154-32