

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 200634

PRIMARY CORNER DESCRIPTION Meander Cor. bet. Secs. 5 & 6

Alias 852580 Description M.C. left bank, U. River  
Alias 062070 Description ENE Pt. DLC #62  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----  
Set Meander post on left bank, from which  
    A Y.Oak 24" dia. bears N.58°W., 87 lks.  
    A W.Oak 10" dia. bears S.52°E., 73 lks.  
(Addison Flint mentioned post and W.Oak in notes for DLC 62)

Frank Cain, Co. Surveyor - Dec. 8, 1914 - Vol. 2 Pg. 267  
-----  
Set Sandstone 3" x 18" x 20" on left bank of River.  
No trees near.  
The above corner was established by orig. BTs which I found standing but girdled and dead.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; Clete Putnam - Dec. 8, 1959 - C.S. File 52/5 - M 16-59  
-----  
Set brass cap at MC mkd.: MC T26S R6W CS BT. County Surveyor's Office, 1959 S6|S5  
New BTs - 18" B.Oak bears S.28°E., 52.8 ft. scribed MC S5 CSBT  
          23" B.Oak bears N.29°W., 49.6 ft. scribed MC S6 CSBT

Fd. Ok by D.Edwards, 1/97, M 126-51.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 7/25/2000 - C.S. File 66/16-27  
-----  
Found - 1959 DCSO Brass cap/iron pipe protrudes 7" above ground.  
          23" now 40" dia., B.Oak with a fully healed blaze, bears N.30°W., 49.6 ft. (rec. N.29°W., 49.6 ft.) 1959  
          18" now 25" dia., B.Oak with a fully healed blaze, bears S.28°E., 52.8 ft. 1959  
New - 24" dia., B.Oak double blazed & scribed "MC S6 CS BT" bears N.55°W., 18.0 ft.  
      8" Ash double blazed & scribed "MC S6 CS BT" bears S.17½°W., 7.8 ft.