

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 200646

PRIMARY CORNER DESCRIPTION M.C. Right Bank Umpqua River

Alias 851510 Description M.C. between Secs. 5 & 6  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set Meander Post, from which  
    A Y.Oak 20" dia. bears N.39 3/4°E., 58 lks.  
    A W.Oak 20" dia. bears N.20½°W., 239 lks.  
Course of River N.35°W. Bank 20 ft. high.

-----  
B.B. Irving, Co. Surveyor - For: R.C. Hutton - Dec. 7-15, 1951  
C.S. File 45/29 - M 7-40

-----  
Set 3" x 6 ft. I.Pipe 5 ft. in ground on Co. Rd. cutbank.  
Marked 30" W.Oak N.45°E., 52.5 ft. mkd. M.C. S5 CS BT.  
    24" B.Oak N.30°W., 119.1 ft. mkd. MC S6 CS BT.  
Position identified from OBT snag, W.Oak N.39 3/4°E., 58 lks.  
chopped out old blaze, part of B visible.

-----  
James W. Byron, Deputy Co. Surveyor - Milo Godfrey; Clete  
Putnam - Dec. 8, 1959 - C.S.File 52/5 - M 16-59

-----  
Set - Brass cap 85 ft. South of Meander Corner mkd:  
    County Surveyor's Office, 1959 W.C. 85' North  
    to MC S6|S5 T26S R6W  
New BTs - 9" Maple bears N.68°W., 33.0 ft. scribed W.C. MC  
    S6 CS BT.  
    9" Maple bears S.20°E., 67.5 ft. scribed W.C. MC  
    S5 CS BT.

-----  
DCSO-GIS Corner visitation - 6/23/2004 - Typed: 1/25/2011 -  
C.S. File 67/33-1

-----  
Monument - BC/IP 1.25"  
Comment - (needs) rehab