

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 300162

PRIMARY CORNER DESCRIPTION Meander Cor. between Secs. 32 & 33

Alias 849710 Description M.C. Right Bank So. Umpqua River  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----

Set Meander post on right bank, from which  
A Y.Oak 20" dia. bears N.20°W., 35 lks.  
A Y.Oak 30" dia. bears N.45°E., 106 lks.

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; Mike  
Stone - July-Aug. 1964 - C.S. File 52/87-79  
-----

Found - 30" old Pine stump N.60°W., 49.5 ft. opened & found  
good scribing "R6" & "S".

No trace of SE tree found.

Location for Meander Corner falls on bedrock in river channel  
and would be under water except in time of low water.

Set - WITNESS CORNER on high bank 60 ft. North of Meander  
Cor. Brass cap at Cor. mkd: County Surveyors  
Office 1964 T26S R6W W.C. M.C. S 32|S 33 60  
feet South to Corner.

New BTs - 16" B.Oak S.80°W., 50.3 ft. mkd. WC MC S 32 CS BT.  
15" W.Oak S.75°E., 3.5 ft. mkd. WC MC S 33 CS BT.

Witness Cor. is alongside Electric Service (on tree) for Motor  
& Irrigation Pump.