

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 28 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>Original - Elder &amp; Gile, Contract #31 dated April, 1853 ----- Set ¼ Sec. post, from which     A Y.Oak 10" dia. bears S.20¾°W., 133 lks.     A Y.Oak 20" dia. bears N.45°E., 40 lks.</p>
<p>J.W. Cole, Deputy Co. Surveyor - May 1921 - F.B. 51 Pg 7 &amp; M 1-69 ----- I renewed this corner from the original bearing trees both of which were alive &amp; standing. I set a 4 x 4 x 40" post also an Iron pipe 1 x 30".</p>
<p>James W. Byron, Deputy Co. Surveyor - March 2-16, 1956 - C.S. File 47/67 ----- Found - ¾" I.P. set by Cole for ¼ cor. Also found SW BT, now a 24" B.Oak &amp; checks bearing &amp; distance to pipe. I open orig. BT &amp; find old face and scribe marks "BT". The NE BT is down. Set - An Iron pipe with brass cap mkd. ¼ cor. 29 28     T26S R6W County Surveyors Office 1956, from which:     16" W.Oak bears S.62°W., 24.0 ft. scribed ¼S29 CSBT     12" W.Oak bears S.57°E., 34.1 ft. scribed ¼S28 CSBT</p>
<p>Found OK, June 1964, M.E.G. C.S. File 52/87-45</p>
<p>Douglas County Surveyors Office - Randall Smith &amp; Stephen Flause - April 8, 1997 - C.S. 64/74-11 ----- Found - 3/4" ID Iron pipe protrudes 6" above ground (1921)     2½" Dia. Brass cap on a 1½" OD iron pipe protrudes 12" above ground is found along east edge of 1921 I.P. (1956).     BC appears to be plumb over 1921 I.P.     10" now 24" dia. 2½' high rotted Oak stump, no scribing visible, bears S.17½°W., 87.9' (rec. S20¾°W. 87.8') OBT     20" now down &amp; rotted Oak, no scribing visible root hole bears N.45°E., 26.4' (agrees with rec.)     16" now 18" Dia. W.Oak, with a fully healed single blaze bears S.60°W. 24' (rec S.62°W 124') 1956     12" now 15" Dia. W.Oak, with a fully healed single blaze, bears S.59°E., 34.1' (rec. S.57°W., 34.1') 1956. continued next page</p>

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

New - 15" dia. D.Fir, double blazed and scribed "¼ S28 CS  
BT", bears S.30½°E., 35.8'.  
7" dia. Madrone, bark scribed "¼ S29 CS BT", bears  
N.33°W., 6.8'.

DCSO-GIS Corner visitation - 6/18/2004 - Typed: 1/26/2011 -  
C.S. File 67/33-1

-----  
Monument - BC/IP 1.25"  
Comment - OK