

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 20, 21, 28 & 29, from which
A Y.oak 20" dia. bears S.71½°E., 122 lks.
A Y.oak 30" dia. bears N.86½°E., 162 lks.
A Y.oak 16" dia. bears N.82°W., 232 lks.
A W.oak 20" dia. bears S.52°W., 198 lks.

J.W. Cole, Deputy - Witnesses: L.H. Smick; Herman Marks
April 15, 1921 - F.B. 50 Page 47

I renewed this corner from the original bearing trees which
bear as follows:
A B.oak 48" standing & bearing scribe marks bears
S.71°30'E., 80.5 ft.
A W.oak 30" standing & bearing scribe marks bears
S.53°30'W., 131.0 ft.
A snag of a B.oak bears scars bears N.80°45'W., 154.8 ft.
A large W.oak down, bearing scars bears N.85°E., 108 ft.
Set - Iron pipe & an Oak post 4 x 4 x 36".

James W. Byron, Deputy Co. Surveyor - March 2-16, 1956
C.S. File 47/67

Found - A 1" I.P. at corner. The orig. BT standing, center
rotted, shows old blaze & checks for bearing &
distance. The NW & SE orig. BTs are now stump
holes only - check for bearing & distance.
New BTs - 14" W.oak N.5°E., 29.8 ft. scribed T26S R6W S21 CSBT
24" W.oak S.43°E., 24.8 ft scribed T26S R6W S28CS BT
12" W.oak (forked) S.6½°W., 75.7 ft scribed S29 CSBT
10" Madrone N.24°W., 8.0 ft. scribed S20 CS BT.

Found OK, June 1964 - M.E.G. - C.S. File 52/87-45
Found OK, July, 1970, R.Gee - M 96-74
Found OK, Sept, 1994, G.Lang - Part. Plat 1994-0095
FD. OK, Apr. 1997, Do. Co. Surveyors Office, CS 64/74-21

DCS0-GIS Corner visitation - 6/18/2004 - Typed: 1/26/2011 -
C.S. File 67/33-1

Monument - 1"
Comment - OK

Fd as per record, 12/24 - Neil Hibbs - 2025-0004 A