

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>Original - Elder &amp; Gile, Contract #31 dated April, 1853 ----- Set ¼ Sec. post, from which     A W.Oak 20" dia. bears S.83½°E., 282 lks.     A W.Oak 20" dia. bears N.55°W., 271 lks.</p>
<p>J.W. Cole, Deputy - April 20, 1921 - F.B. 50 Pg. 48 ----- I renewed this corner from original bearing trees:     A W.Oak S.83½°E., 186.1 ft.     A W.Oak down decayed N.55°W., 178 ft. Set - A 4 x 4 x 40" Oak post and marked a new tree:     A W.Oak 10" dia. bears S.12°30'W., 33 ft.</p>
<p>Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; Mike Darby; Mike Stone - July, 1964 - C.S. File 52/87-50 ----- Found - 3/4" I.P. in mound of rocks. No record of I.P. in Corner renewal records, but is shown on Cole's map of survey, M 1-69. Old stump hole with fragments of Oak lying around it, S.83½°E., 186 ft. fits orig. SE BT. Possible stump hole S.12½°W., 33 ft. fits Cole's new BT. Location also checks calls in Gov't field notes to draw North of corner. Did not set brass cap. New BTs- 27" B.Oak N.70°W., 289.2 ft. mkd. "¼ S20 CS BT".         7" Madrone N.20°E., 288.0 ft. mkd. "¼ S21 CS BT".         A fence line, approx. N &amp; S, bears East 29 ft.</p>
<p>Douglas Co. Surveyors Office - Randall Smith; Stephen Flause April 4, 1990 - C.S. File 64/9-4 ----- Found - ¾" I.D. I. Pipe found 1" below ground.         27" now 35" dia. W.Oak with a fully healed single blaze bears N.70°W., 289.2 ft.         No other BTs found. Set - The found ¾" I.P. is referenced, I.P. measures 25 ft long when removed. Set - A 2 3/8" dia. brass cap on a 1¼" O.D. x 31" long I.P. is set at referenced position. BC/IP protrudes 4" above ground with found ¾" I.P. set 2" below ground along North side of BC/IP. Cap is stamped "Douglas County Surveyors T26S ¼ S20 S21 R6W 1990 Office". New BTs- 3" dia. W.Oak double blazed &amp; scribed "X BT" bears S.55¼°W., 73.2 ft. Continued next page</p>

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

4" dia. W.Oak double blazed & scribed "X BT" bears  
N.88¼°E., 53.9 ft.  
6" dia. Madrone bark scribed "¼ S21 CS BT" bears  
S.46°E., 17.6 ft.

DCSO-GIS Corner visitation - 6/18/2004 - Typed: 1/26/2011 -  
C.S. File 67/33-1

-----  
Monument - BC/IP 1.25"  
Comment - (needs) rehab