

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post corner to Secs. 16,17, 20 and 21, from which

A Y.oak 10" dia. bears N.27¼°W., 34 lks.

A Y.Oak 9" dia. bears N.41½°E., 59 lks.

A Y.Oak 6" dia. bears S.75½°E., 27 lks.

A W.Oak 15" dia. bears S.25½°W., 47 lks.

J.W. Cole, Deputy - April 20, 1921 - F.B. 50 Pg. 49

I renewed this corner from the rotting remains of the orig. BTs one of which Mr. James Cooper testifies that he had seen scribe marks on several years previously. The remains of the trees checked for direction & distances given in the field notes. I set -

An iron pin ½" x 36" & marked new trees:

A W.Oak 20" dia. N.42°15'E., 122.3 ft.

A W.Oak 30" dia. N.17°50'W., 224.2 ft.

Milo E. Godfrey, Deputy - Mike Stone - June, 1964 -
C.S. File 52/87-48

Found - ½" iron rod set by Cole in 1921.

W.Oak (now 24" dia.) N.42¼°E., 122.3 ft. Both axe scars plainly visible. Tree alive, good cond.

Badly rotted Oak stub N.18°W., 224.2 ft. Portion of a scribe mark visible on surface.

Did not set brass cap.

New BTs - 10" W.Oak N.60°W., 32.0 ft. mkd. "T26S R6W S17 CSBT.

11" W.Oak S.24°W., 76.4 ft. mkd. "T26S R6W S20 CSBT.

15" W.Oak S.27°E., 102.5 ft. mkd. T26S R6W S21 CSBT.

DCSO-GIS Corner visitation - 6/16/2004 - Typed: 1/26/2011 -
C.S. File 67/33-1

Monument - ½" rebar

Comment - ok