

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
 A Y.Oak 18" dia. bears N.33°W., 24 lks.
 A Y.Oak 8" dia. bears S.62½°E., 13 lks.

Milo E. Godfrey, Deputy - Wm. Stoffel; M. Darby; M. Stone
July 1964 - C.S. File 52/87-60

Found - Old B.Oak N.33°W., 15.8 ft. This tre was opened
 many years ago & entire center rotted away.
 Small fragments of old face found, some show-
 ing definite axe marks. No scribing found.
 Portion of root system (above ground) with black
 oak growing out of one side. Stump hole
 visible S.62½°E., 8.6 ft.
From this evidence set corner.
Set - Brass cap at corner mkd: County Surveyors Office
 1964 T 26S R6W ¼ S | S
 8 | 9
New BTs - 15" D.Fir N.18½°W., 13.3 ft mkd. ¼ S 8 CS BT (above
 fence)
 14" W.Oak N.30°E., 23.7 ft. mkd. ¼ S 9 CS BT.
 An Iron rod (1" dia.) apparently set for corner
 bears N.44°E., 5.6 ft.
An E & W fence line is 12.4 ft. North of corner.

Fd. brass cap, 2 BTs, & 1" I.R. -Russell T. Pinard - April
1979 - M 76-66

DCSO-GIS Corner visitation - 7/16/2004 - Typed: 1/26/2011 -
C.S. File 67/33-1

Monument - BC/IP 1.25"
Comment - ok

1