

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original - Elder & Gile, Contract #31 dated April, 1853 ----- Set ¼ sec. post, from which A W.Oak 20" dia. bears S.5¾°E., 275 lks. A Y.Oak 13" dia. bears N.68½°W., 259 lks.</p>
<p>J.W. Cole, Deputy Co. Surveyor - May, 1921 - M 1-69 and F.B. 50 Pg. 68 ----- I set an Oak post 4 x 4 x 40", also an Iron pipe 1" x 30" from which a stump of an original BT bears S.5¾°E., 181.5 ft. A snag of BT bears scribe marks N.68°30'W., 171 ft. Marked new trees as follows: A B.Oak 16" dia. bears N.68°30'W., 4 ft. A Double W.Oak 24" dia. bears South 68.5 ft.</p>
<p>James W. Byron, Deputy Co. Surveyor - Milo Godfrey; S.A. Bilow - February 11, 1959 - C.S. File 49/121-3 ----- Found - 1" Iron pipe at corner & both BTs as recorded by Cole, 1921 . The NW BT down. I open now 30" W.Oak South 68.5 ft. & find good scribing. New BTs - 20" W.Oak bears N.40½°W., 22.8 ft scribed ¼S21 CSBT 8" Laurel bears S.11°E., 5.9 ft scribed ¼ S28 CS BT</p>
<p>Milo E. Godfrey, Deputy - Mike Stone - June 17, 1964 - C.S. File 52/87-37 ----- Found - ¾" I.P, bent over. 20" W.Oak N.40½°W., 22.8 ft. some scribing visible in not completely healed scar. 30" W.Oak, Cole's tree, South 68.5 ft. scribing visible in opened scar. All traces of Laurel to the SE have completely vanished. New BT - 18" W.Oak S.51°E., 28.5 ft. mkd. ¼ S 28 CS BT.</p>
<p>Douglas Co. Surveyors Office, Gregory Quibell, Deputy - Terrie Plouff; Teresa Buley - Dec. 14, 1981 - C.S. 61/29-43 ----- Found - Bent over ¾" I.P. buried approx. 0.3 ft west of old fence post. 20" now 24" W.Oak with well healed blazes, bears N.40½°W., 22.8 ft. 30" now 26" double W.Oak with well healed blaze bears South 68.5 ft. continued next page</p>

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

18" now 18" double W.Oak with well healed double blaze bears S.51°E., 28.5 ft.
Set - I reference point where ¾" I.P. goes straight down into ground & then set 1" x 30" I.P. with brass cap attached in its place. I bury the ¾" I.P. along East side of BC. Cap lies 0.3 ft. west of fence corner. Cap protrudes 3" out of small mound of stones & is marked: "Douglas Co. Surveyor T26S ¼ S21 S28 R6W 1981".
(sketch in file)

Douglas County Surveyors Office - Randall Smith; Stephen Flause - February 16, 1984 - C.S. File 62/16-8

Found - Iron pipe with brass cap.
20" now 24" W.Oak w/well healed double blaze bears N.40½°W., 22.8 ft.
30" now 26" double trunk W.Oak w/well healed blaze bears South, 70.0 ft. to center of crown. (Rec. 68.5 ft. is to center of scribed north trunk.)
18" now 18" double trunk W.Oak w/well healed double blaze bears S.51°E., 28.9 ft. to center of crown. (Rec. 28.5 ft. is to center of scribed north trunk)
New - Found & tied a 5/8" I.Rod (property corner) bears N.89½°E., 64.7 ft.

Fd Brass cap & 2 BTs. - Ken Hoffine, January 1992, M 114-79
Found Brass cap - Don Bentz, May 1994, M120-14
Found BC & 2 BTs. - B.Rogers March 1995, 1995-0064
Found OK by Bentz, Sept. 1996 - Subd. Plat Vol. 19 Pg. 11 A&B

DCS0-GIS Corner visitation - 6/21/2004 - Typed: 1/27/2011 - C.S. File 67/33-1

Monument - BC/IP 1.25"
Comment - OK

Fd. BC by G. Lang, 2/2015 - 2015-0006
Fd. BC by D Feigel 6/2020 - 2020-0027A