

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----

Set ¼ sec. post, from which

A Y.Oak 36" dia. bears N.35½°W., 129 lks.

A Y.Oak 48" dia. bears S.21¾°W., 267 lks.

J.W. Cole, Deputy Co. Surveyor - May, 1921 - F.B. 50 Pg. 62  
and M 1-69  
-----

I renewed this corner from the orig. BTs. The tree N.35°30'W.  
was alive & standing, showing scars. The tree S.21°45'W.,  
was down and nearly burned up. The directions & distances  
checked. I set a 4 x 4 x 40" post and erected a mound of  
rock. Marked a new tree:

A B.Oak 14" dia. bears S.35°30'W., 11 ft.

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; Mike Stone  
July, 1964 - August 1964 - C.S. File 52/87-81  
-----

Found - Mound of rock set by Cole.

22" B.Oak S.35½°W., 11.0 ft. opened & found good  
scribe. (Cole's BT)

B.Oak N.35½°W., 85.1 ft. dead & down (Orig.BT.)

Stump hole & remnants of very large Oak, S.22°W.,  
176.2 ft. (Original)

Set - Brass cap at cor. mkd. County Surveyors Office, 1964  
T26S R6W S16 S22.

New BTs - 20" W.Oak N.67°W., 7.9 ft. mkd. ¼ S16 CS BT.

24" B.Oak S.82°E., 7.6 ft. mkd. ¼ S21 CS BT.

Corner is in draw. Re-erect rock mound around brass cap.

Douglas County Surveyors Office - Randall Smith & Stephen  
Flause - April 10, 1997 - C.S. 64/74-18  
-----

Mon. Fd.- 2½" dia. Brass cap on a 1½" O.D. iron pipe protrudes  
15" above ground, base of iron pipe is  
surrounded by a 2' dia. mound of stone. 1964

Accessories Fd.-

36" now 30" dia. down and rotted Oak, no scribing  
visible, Root hole agrees well with rec  
"N.35½°W., 85.1' OBT

Orig. SW BT is gone

(Cont. Next Page)

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

14" now 25" dia. down B.Oak, with a healed blaze,  
root hole bears S.35½°W., 11' (agrees with  
rec.) 1921  
20" now 24" dia. W.Oak, with a fully healed double  
blaze, bears N.67°W., 7.9' (agrees with rec.)  
1964  
24" now 24" dia. B.Oak, with a fully healed double  
blaze, bears S.82°E., 7.6' (agrees with rec.)  
1964  
New Accessories -  
10" dia. D.Fir, double blazed and scribed "¼ S16 CS  
BT", bears N.20°W., 24.8'.  
8" dia. D.Fir, double blazed and scribed "¼ S16 CS  
BT", bears N.65°E., 26.8'.