

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set $\frac{1}{4}$ sec. post, from which
A Y.Oak 20" dia. bears S.10 $\frac{1}{2}$ °E., 34 lks
A Pine 40" dia. bears N.64 $\frac{1}{4}$ °E., 106 lks.

Milo E. Godfrey, Deputy - Wm. Stoffel; M. Darbey; M. Stone
July 1964 - C.S. File 52/87-62

Found - 40" Pine snag N.64 $\frac{1}{4}$ °E., 70.0 ft. Dead many years
& badly rotted, except for face which is
pitched over, good scribing " $\frac{1}{4}$ S".
Stump hole with remnants of old Oak stump S.10 $\frac{1}{2}$ °E.,
28.4 ft. (43 lks. instead of 34 lks.)

Set - Brass cap at Cor. mkd. County Surveyors Office 1964
T26S R6W $\frac{1}{4}$ S 9
S16

New BTs- 10" Madrone S.72°W., 19.0 ft. mkd. $\frac{1}{4}$ S16 CS BT.
18" D.Fir N.71 $\frac{1}{2}$ °W., 32.7 ft. mkd. $\frac{1}{4}$ S 9 CS BT.
Corner lies on SE slope of hill approx. 200 ft. NW of Valley.