

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 4; & 33 of T25-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
 A Y.Oak 20" dia. bears N.27°W., 27 lks. dist.
 A Y.Oak 14" dia. bears S.2°W., 25 lks. dist.

Milo E. Godfrey's Crew - Vernon Tracy; Mike Stone
February, 1963 - C.S. File 49/123-73

Found - 20" B.Oak snag S.2°W., 16.5 ft. with good scribe.
 29" B.Oak N.27°W., 17.8 ft. down, dead & rotting.
 Didn't open.

Set - Brass cap at cor. mkd. County Surveyors Office 1963
 T25S R6W ¼ S 33
 T26S R6W S 4

New BTs - 14" D.Fir bears S.70°W., 23.3 ft. mkd. ¼ S 4 CS BT.
 16" D.Fir bears N.55°W., 14.4 ft. mkd. ¼ S33 CS BT.
This corner is 1.5 ft. S. of E-W fence line & approx. 165 ft.
E. of top of ridge which bears N. & S.

Doug. Co. Surveyors Office - Randall Smith; Stephen Flause
September 4, 1991 - C.S. File 64/17-4

Found - A 2½" dia. DCS0 brass cap on a 1¼" O.D. iron pipe
 protruding 9" above ground.
 20" Oak, now root hole, a fallen rotted 20" dia. Oak
 Has an open rotted blaze, illegible scribing
 visible. Root hole bears S.2°W., 16.5 ft.
 29", now root hole, a fallen out of position 26"
 dia. rotted Oak, has a previously opened rotted
 blaze, no scribing visible. Root hole bears
 N.27°W., 17.8 ft. (Orig. BT.)
 14" now 24" dia. 1 ft. high D. Fir stump with a
 healed lower blaze, bears S.70°W., 23.3 ft.
 16" now 20" dia. 2½ ft. high D.Fir stump with a
 partially healed blaze, no scribing visible,
 bears N.55°W., 14.4 ft.

New BTs - 7" dia. D.Fir double blazed & scribed "¼ S33 CS BT"
 bears N.72½°E., 27.3 ft.
 6" dia. D.Fir double blazed & scribed "¼ S33 CS BT"
 bears N.80°W., 43.0 ft.
 6" dia. W.Oak double blazed & scribed "¼ S4 CS BT"
 bears S.80°W., 72.9 ft.)

(Cont. Next Page)

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 4; & 33 of T25-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" dia. D. Fir double blazed & scribed ¼ S4 CS BT"
bears S.29½°E., 74.3 ft.
Corner lies 150 ft. East of a N-S running ridge and 1 ft.
South of an E-W fence line. (Sketch in C.S. File 64/17)

Found OK, April 1994 by Pieske - M 118-80.

DCS0-GIS Corner visitation - 7/6/2004 - Typed: 1/27/2011 -
C.S. File 67/33-1

Monument - BC/IP 1.25"
Comment - OK