

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 400179

PRIMARY CORNER DESCRIPTION Meander Cor. E. bdy. Sec. 33

Alias 849630 Description M.C. Right bank Umpqua River
Alias 042080 Description Point on S bdy DLIC #42
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(Co. records, Vol. 11 Pg. 4551)

Set Meander post, from which
A Y.Oak 18" dia. bears N.47½°E., 149 lks.
A W.Oak 18" dia. bears N.56¾°W., 124 lks.

N.E. Richardson; H.L. Eppstein Jr. - Doug. Co. Surveyors Off.
Nov. 13, 1940 - C.S. 37/105

Set the corner from one old BT namely a Y.Oak N.47½°E., 149
lks. For this corner, set an Oak post 4 x 4 x 48" marked
M. C. C.S. 33 and 34, from which
Triple W.Oak 14" dia. mkd. M.C. C.S. B.T. bears
N.43½°E., 29.0 ft.

Milo E. Godfrey, Deputy; Mike Stone - June 17, 1964 - C.S.
File 52/87-38

Found - W.Oak now 15" dia. N.43½°E., 29.0 ft. shows very
plain axe scars. Tree in good condition.
No trace of original BT found.
Set - Iron pipe with brass cap mkd "County Surveyor's
Office 1964 T 26 S R 6 W M.C. S33|S34".
The brass cap at the corner for sections 27, 28, 33 and 34
bears North 97.0 ft.
No suitable trees near in Sec. 33.

Douglas Co. Surveyors Office - Stephen J. Flauser; R.W. Smith
December 5, 1986 - C.S. 62/38-5

Monument position occasionally covered by high water of Umpqua
River. Monument from 1964 apparently washed away. After
reasonable search of area, monument not found. No original BTs
found.

Found - A triple W.Oak 14" dia. now a 15" DBH (on most
southerly trunk)W.Oak with a fully healed
double blaze bears N.43½°E., 29.4 ft. to center
of most southerly trunk at blaze height. (Rec.
N.43½°E., 29.0 ft., to a face measurement).

(Cont next page)

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 400179

PRIMARY CORNER DESCRIPTION M.C. East bdy Sec 33

Alias 849630 Description Meander Cor. Right bank U. River
Alias _____ Description 042080 Point of S. bdy D.C. #42
Alias _____ Description _____
Alias _____ Description _____

Found - The brass cap monument for Sections 28, 27, 33, 34, bears North, 97.0 ft.

Set - Using the found BT, Northeast, and the found section cor, S28 S27 S33 S34, bearing North, 97.0 ft. the meander corner position is reestablished. Remonumented with a DCSO 2 3/8" dia. brass cap mkd. "T26S R6W S33|S34 MC 1986" on a 1 3/8" dia. 32" long galv. I.P set protruding 5" above ground & surrounded by a 2 ft. dia. mound of stone.

New BTs - A 4" DBH W.Oak scribed X BT bears S.89¼°E., 28.7 ft.
A 9" DBH W.Oak scribed MC S33 CS BT on a double blaze bears S.89½°W., 85.6 ft.

(See DCSO Geodetic Conrtal Book for coordinates)