

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original - Elder & Gile, Contract #31 dated April, 1853 ----- Set ¼ sec. post, from which A W.Oak 15" dia. bears S.29°E., 103 lks. A Y.Oak 16" dia. bears N.13°W., 100 lks.</p>
<p>Milo E. Godfrey, Deputy - Wm. Stoffel; Mike Darby; Mike Stone - June 1964 - C.S. File 52/87-30 ----- Found - Stump hole & rotted down Oak N.13°W., 66.0 ft. shows overgrowth of upper & lower scars. Faint reverse scribing visible on upper scar portion of "S". Stump hole & center portion of W.Oak S.29°E., 68.0 ft. outside rotted away, no marks visible. Set - Brass cap mkd. County Surveyors Office 1964 T 26 S R 6 W ¼ S S 16 15 New BTs - 15" I.Cedar S.20°W., 4.4 ft. mkd. "¼ S 16 CS BT". 18" Madrone N.54°E., 24.2 ft. mkd. ¼ S 15 CS BT. Corner lies 3.5 ft. West of N & S fence line.</p>
<p>Fd. Ok by D.Edwards, 11/96, M 126-9. Fd. Ok by N. Hibbs 7/2004 M144-74 FD. Ok by D. Edwards 11/2006 - M151-66</p>
<p>DCSO-GIS Corner visitation - 7/20/2004 - Typed: 1/27/2011 - C.S. File 67/33-1 ----- Monument - BC/IP 1.25" Comment - (needs) rehab</p>
<p> </p>