

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to secs. 9, 10, 15 & 16, from which
A Pine 40" dia. bears S.45½°E., 292 lks.
A Y.Oak 8" dia. bears N.74°E., 149 lks.
A Y.oak 16" dia. bears N.74½°W., 50 lks.
A W.Oak 12" dia. bears S.56½°W., 170 lks.

James W. Byron, Deputy Co. Surveyor; Milo Godfrey; S.A. Bilow
February 11, 1959 - C.S. File 49/121-5

Found - Orig. 16" now 24" Oak snag, center rotted N.74½°W.
33.0 ft. I find good reverse scribe marks near
base "T".

Find large stump hole that checks bearing &
distance for orig. SE. BT.

No trace of orig. SW or NE BTs found.

Set - Brass cap at cor. mkd: S9|S10 T26S R6W County
Surveyor's Office S16|S15 1959

New BTs - 10" R.Fir bears S.46½°E., 60.1 ft. scribed S15 T26S
R6W CS BT.

14" R.Fir bears S.78°W., 30.0 ft. scribed S16 T26S
R6W CS BT.

14" R.Fir bears N.46½°W., 20.6 ft. scribed S9 T26S
R6W CS BT.

24" Cedar bears N.57½°E., 51.3 ft. scribed S10 T26S
R6W CS BT.

Milo Godfrey, Deputy - Wm. Stoffel; Mike Darby; Mike Stone
May 1964 - C.S. File 52/87-18

Found - Brass cap & 3 BTs in good condition. SE BT now dead
24" Cedar N.57½°E., 51.3 ft.
14" D.Fir N.46½°W., 20.6 ft.
14" D.Fir S.78°W., 30.0 ft.

New BT - 8" W.Oak S.53½°E., 95.4 ft. mkd. T26S R6W S15 CSBT.

DCS0-GIS Corner visitation - 7/16/2004 - Typed: 1/27/2011 -
C.S. File 67/33-1

Monument - BC/IP 1.25"
Comment - (needs) rehab

continued next page

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 & 16

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Adam DeGroot - For: Oshell -June 2021 - M178-30

Found - A 1¼" iron post by DCS0 in 1959 loosely set 18" out of ground and leaning severely northerly downhill. I reference base of post at the flanges and reset with top projecting 14" above the ground, with 2½" brass cap (properly) stamped.

From which BTs by Byron in 1959 -

A 43" Cedar bears N.57°30'E., 51.3 ft with healed blaze

A 18" D.Fir stump bears N.46°30'W., 20.6 ft with healed blaze

A 20" D.Fir stump bears S.78°W., 30.0 ft with healed blaze

A BT by Godfrey in 1964 -

A 15" W.Oak bears S.53°30'E., 95.4 ft with healed blaze (BTs were measured for new diameters in 2013, with DCS0 records listed)

NAD83 (CORS96)

Lat: 43°18'58.58738" N 123°24'22.88373"W