

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Corner for Secs. 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
 A W.Oak 15" dia. bears N.47°W., 24 lks.
 A W.Oak 24" dia. bears N.60°E., 78 lks.

Milo E. Godfrey, Deputy - Wm. Stoffel; Mike Darby; Mike Stone - May 1964 - C.S. File 52/87-26

Found - W.Oak now 26" dia., N.47°W., 15.8 ft. opened & found scribing "¼" on badly rotted face.
No trace of N.E. tree found.
Set - Brass cap mkd: County Surveyors Office 1964 T26S
 R6W ¼ S | S
 9 | 10
New BTs - 14" D.Fir N.82°W., 24.4 ft. mkd "¼S9 CS BT."
 W.Oak S.33°E., 53.3 ft. mkd. ¼ S10 CS BT.
Corner lies in N & S fence line approx. 23 ft. South of fence corner - fences South & West.

DCSO-GIS Corner visitation - 7/15/2004 - Typed: 1/27/2011 - C.S. File 67/33-1

Monument - BC/IP 1.25"
Comment - (needs) rehab

1