

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 & 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
A W.Oak 24" dia. bears N.57¼°W., 136 lks.
A W.Oak 8" dia. bears S.64½°E., 314 lks.

H.L. Eppstein, Co. Surveyor - T.F. Powers; B.A. Lane
Sept. 9, 1930 - C.S. File 14/61

Set corner from old BT, Oak down, but scribe marks plain.
Set a 4 x 4 x 36" Oak stake. Marked new witness trees as follows:
W.Oak 8" dia. bears N.54°W., 59 ft.
W.Oak 6" dia. bears N.22°E., 66 ft.

A.R. Evans - Surveyor - Witnessess: Bob Matthews; E.A. Jennie
November 1949 - C.S. File 43/167 & M 16-25

Found 2 O.B.T's in good shape.
Set ¾" x 36" Iron rod for corner, from which O.B.T's
Oak N.54°W., 59.0 ft.
Oak N.22°W., (66.0 ft.) approx. 66 lks.

Milo E. Godfrey, Deputy - Wm. Stoffel; Mike Darby; Mike Stone
May 1964 - C.S. File 52/87-28

Found - W.Oak now 13" dia. N.22°E., 66 ft. opened & found
good scribing "¾".
W.Oak now 18" dia. N.54°W., 59 ft. Shows good scar,
Did not open.
Did not find iron rod set by Evans, nor Oak stake
set by Eppstein.
Position for corner falls in center of creek, as measured from
bearing trees.
Set - Witness corner 25 ft. North. Brass cap mkd: County
Surveyors Office 1964 T 26 S R 6 W W.C. 25 ft.
South to ¼ $\frac{S|S}{4|3}$
New BTs - 15" D.Fir N.5°W., 25.6 ft. mkd. WC ¼ S4 CS BT.
12" D.Fir N.11°E., 50.0 ft. mkd WC ¼ S3 CS BT.

