

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Corner for Secs 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

| |
|--|
| <p>Original - Elder & Gile, Contract #31 dated April, 1853 ----- Set ¼ sec. post, from which A W.Oak 15" dia. bears S.75¼°E., 232 lks. A W.Oak 16" dia. bears N.12¼°E., 52 lks.</p> |
| <p>James W. Byron, Deputy Co. Surveyor - Milo Godfrey; S.A. Bilow - Feb. 11, 1959 - C.S. File 49/121-6 ----- Found - Orig. 16" now 30" W.Oak N.12½°E., 34.4 ft., I open & find good scribing "¼S". Orig. 15" now 28" W.Oak checks bearing & distance S.75¼°E., 153.1 ft. I do not open. Set - Brass cap at corner mkd. ¼ S10 S15 T26S R6W County Surveyor's Office, 1959. New BTs - Remark orig. now 30" W.Oak N.12½°E., 34.9 ft. scribed ¼ S10 CS BT. 12" W.Oak bears S.61°W., 28.6 ft. scribed ¼ S15 CSBT</p> |
| <p>Found OK, May 1964, M.E.G. C.S. 52/87-19 Fd. Ok by D.Edwards, 11/96, M 126-9.</p> |
| <p>Adam DeGroot - For: Oshell -June 2021 - M178-30 ----- Found - A 1 3/8" iron post, by DCS0 IN 1959, firmly set & projecting 15" above the ground, with a 2 1/2" brass cap (properly) marked: From which the Original BTs - A 30" W.Oak bears N.11°E., 35.0 ft w/healed lower and rotted upper blaze [N.12¼°E., 52 lks] A root hole of down 28" W.Oak bears S.75°30'E., 154.3 FT [S.75¼°E., 232 lks] And a BT by DCS0 IN 1959 - A 14" W.Oak bears S.61°45'W., 28.9 ft w/healed dbl blaze [S.61°W., 28.6'] New BTs - A 11" D.Fir bears S.5°E., 34.2 ft scribed "¼ S15 BT" on dbl blaze A 12" D.Fir bears N.61°45'W., 71.2 ft scribed "¼ S10 BT" ON DBL BLAZE NAD83(CORS96) Lat: 43°18'58.50021" N 123°23'47.24524" W</p> |
| |