

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
 A Laurel 18" dia. bears S.70½°E., 31 lks.
 A Laurel 14" dia. bears N.70°W., 46 lks.

A.R. Evans - Bob Matthews; E.A. Jennie, Witnesses
Nov. 1949 - C.S. File 43/167 - M 16-25

Found O.B.T. stump badly rotted, faint scribe mark visible
on blaze on root, S.70½°E., 31 lks.
Set - 1" I.Pipe from which
 34" Fir bears N.9°E., 4.5 ft. mkd. ¼ S 3 C.S.B.T.
 No other suitable trees available.

Milo E. Godfrey, Deputy - Wm. Stoffel; Mike Darby; Mike Stone
June, 1964 - C.S. File 52/87-31

Found - 1" I.P. set by Evans in 1959.
 34" Fir N.9°E., 4.5 ft. mkd. by Evans (Bark scribed
 "T 26 R 6 ¼ S 3 CS BT")
 Rotten Laurel stump S.70½°E., 20.5 ft. no markings
 visible at present.
 No trace of N.W. tree found.
New BT - 13" D.Fir S.53°E., 50.4 ft. mkd. "¼ S10 CS BT".
 Posted yellow tag along trail on top of ridge 600
 ft. South of corner.