

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 443200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 & 34

Alias 440200 Description (True corner PLSS #)
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original - Elder & Gile, Contract #31 dated April, 1853 ----- Set ¼ sec. post, from which A W.Oak 24" dia. bears S.72°E., 286 lks. A W.Oak 18" dia. bears N.33°E., 62 lks.</p>
<p>H.L.Eppstein, Co. Surveyor - Bert Lane; Claude Crocker - July 10, 1927 - C.S. File 6/44 ----- Set post for corner from old BT, an Oak, mkd. new BTs W.Oak 8" S.46°30'W., 13.9 ft. W.Oak 6" N.4°W., 12.7 ft.</p>
<p>J.R. Daugherty - Feb. 10, 1949 - C.S. 40/216 ----- Corner reset from O.B.T., set an iron pin 5/8" x 24". 8" W.Oak N.7°36'W., 12.7 ft. (set by Eppstein, 1927) 10" W.Oak S.41°41'W., 13.9 ft. (set by Eppstein, 1927) 24" W.Oak N.33°E., 40.55 ft. (set on original survey)</p>
<p>James W. Byron, Deputy - Dale McFarland; J. Powell August 11, 1961 - C.S. File 52/87-3 ----- Found - 5/8" I. Rod at corner & now 12" W.Oak N.4°W, 12.7 ft. shows good scribing. Now 8" Oak snag S.46°W., 13.9 ft. shows good scribing New BT - Rescribe old BT, now 30" W.Oak: ¼ S27 CS BT N.38½°E., 41.4 ft.</p>
<p>Found OK, June 1964, M.E.G. C.S. 52/87-39</p>
<p>Douglas Co. Surveyors Office - Vernon R. Tracy; Terry Connell July 8, 1965 - C.S. File 52/87-99 ----- Due to Road construction, we set Witness Corner 175.0 ft. East of ¼ corner recorded in 1961, which is: 5/8" iron rod for corner & BTs: 12" W.Oak N.4°W., 12.7 ft. shows scribe. 8" Oak snag S.46°W., 13.9 ft. shows scribe. Set - Brass cap at cor. mkd. County Surveyor's Office 1965 T26S R6W W.C. 175 ft. W. to ¼ S 27 S 34. New BTs - 6" Laurel S.61°E., 13.8 ft. mkd. W.C. ¼ S34 CS BT. 6" B.Oak N.40½°E. 101.0 ft. mkd. WC ¼ S27 CS BT Witness corner lies approx. 25.0 ft. East of small ravine.</p>
<p>continued next page</p>

