

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. 34 & 35; 2 & 3 of T27-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post (on summit of hill N.20°E & S.20°W) cor. to secs.
2, 3, 34 & 35, from which

- A W.Oak 6" dia. bears S.57¾°W., 67 lks.
- A Y.Oak 6" dia. bears N.86°W., 43 lks.
- A Y.Oak 10" dia. bears N.10°E., 120 lks.
- A Y.Oak 8" dia. bears S.73°E., 136 lks.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; Clete
Putnan - February 1961 - C.S. File 49/79-41

Found - Orig. 6" now 18" W.Oak S.57½°W., 44.2 ft. center
rotted.
Orig. 10" now 34" B.Oak N.10°E., 79.2 ft. We open &
find good scribing "W".
Orig. 6" now 24" B.Oak N.86°W., 28.4 ft. shows scar.
Orig. 8" now 24" B.Oak S.73°E., 89.8 ft. shows scar.
Set - Brass cap at cor. mkd. County Surveyor S34|S35 T26S
R6W Office, 1961 S 3|S 2 T27S
New BTs - 24" B.Oak N.86°W., 28.4 ft. (OBT) scribed S34 T26S
R6W CS BT.
12" W.Oak N.20°E., 84.0 ft. scribed S35 T26S R6W
CS BT.
9" B.Oak S.15°E., 53.0 ft. scribed S2 T27S R6W CSBT.
9" W.Oak S.29°W., 14.7 ft. scribed S3 T27S R6W CSBT.

Found OK, Bruce Rogers, November, 1982 - M 93-27