

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. to Secs. 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
A W.Oak 8" dia. bears S.85½°E., 994 lks.
A W.Oak 18" dia. bears N.76¾°E., 524 lks.
No tree near West of line.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy; Wm.
Stoffel; Mike Stone - July 1964 - C.S. File 52/87-70

Found - 15" W.Oak S.85½°E., 656.0 ft. cut open & found good
scribing "T".
34" W.Oak N.76¾°E., 345.8 ft. shows very plain scar.
Didn't open.

Set - Brass cap at cor. mkd. County Surveyors Office 1964
T26S R6W ¼ S34|S35

New BTs - 26" W.Oak S.16½°E., 47.2 ft. mkd. ¼ S35 CS BT.
16" W.Oak N.85½°E., 83.3 ft. mkd. ¼ S35 CS BT.
No trees readily available west of line.

Corner is 37 ft. North of E. & W. fence line.

Found OK, Bruce Shaner, Oct. 1996 - C.S. 65/8-15 (Land
Partition 1996-0105)