

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 26, 27, 34 & 35, from which
An Ash 12" dia. bears N.67°E., 365 lks.
A W.Oak 7" dia. bears N.43½°W., 274 lks.
A W.Oak 7" dia. bears S.25¼°W., 865 lks.
A W.Oak 8" dia. bears S.8°54'E., 1061 lks.

H.L. Eppstein, Co. Surveyor - Bert Lane; N.E. Richardson;
John Marks; John Thennes; C.B. Calkins - July 17, 1937
C.S. File 15/6

Set 2" x 5 ft. I.Pipe from 24" W.Oak N.43½°W., 180.8 ft.,
old BT scribe marks plain. Also, stump of Ash in evidence
Marked new BTs as follows:
12" W.Oak S.46°E., 70.7 ft. mkd. S35 CS BT.
10" W.Oak N.60¾°E., 261.3 ft. mkd. S36 CS BT.
8" W.Oak N.4°36'W., 436.6 ft. mkd. T26S R6W S27 CSBT.

Milo E. Godfrey, Deputy - Mike Stone, June 17, 1964
C.S. File 52/87-41

Found - 1 I.P. (instead of 2" as called for) corner pipe
extends approx. 18" above ground surface.
Old W.Oak(now 26" dia.) N.43½°W., 180.8 ft., scar
healed where it was previously opened.
12" W.Oak N.60¾°E., 261.3 ft. upper scar visible,
scribing "BT" visible below on rotting face.
Did not find Eppstein's new BT to NW.
New BT - 10" W.Oak S.14°W., 333.8 ft. mkd. T26 S R6W S34
CS BT.

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - Mar. 18, 1997 - C.S. 64/74-4

I.P. from 1937 DCSO renewal not found
BT's Fd.- 7" now 26" dia. W.Oak, with a previously opened
fully healed blaze, bears N.43½°W., 180.8'
(agrees with rec.) OBT
12" now 13" dia. W.Oak, with a fully healed single
blaze, bears S.46°E., 70.7' (agrees with rec.)
(Cont. Next Page)

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

10" now 10" dia. W.Oak, with a partially healed rotted blaze no scribing visible, bears N.60 3/4°E., 260.7' (rec. N.60 3/4°E., 261.3' good slope measurement)
10" now 13" dia. dead W.Oak, with a fully healed blaze, tree is standing in water at south end of a pond, bears S.14°W., 333.8' (agrees with rec.) 1964
Mon. Set- 2 3/8" dia. brass cap on a 1 3/8" O.D. by 32" long iron pipe is set at a position determined from bearing trees. Brass cap protrudes 2" above ground. DOUGLAS COUNTY SURVEYORS
T26S R
S27|26 6
S34|S35 W
1997
OFFICE
New Bt's- 12" Ash double blazed and scribed "T26S R6W S35 CS BT", bears S.68°E., 107'.
Corner lies in open field approx 200' north of a pond.

Found OK by J. Estabrook, Aug. 2003 2003-0068 A-B
Fd. BC by B Knapp - Sept 2022 - M181-41