

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 14, 15, 22 & 23, from which
A Y.Oak 18" dia. bears N.68°E., 70 lks.
A W.Oak 12" dia. bears S.76¾°E., 60 lks.
A W.Oak 18" dia. bears S.8°W., 336 lks.
A Y.Oak 40" dia. bears N.27°W., 312 lks.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; S.A.
Bilow - Feb. 11, 1959 - C.S. File 49/121-3

Found - Orig. 18" now 24" Oak. Stump shows good reverse
scribe marks below cut, N.8°W. I find N.9½°W.
Orig. 48" now 60" B.Oak. I open & find good scribing
"S", N.27°W., I find N.25½°W., 205.9 ft.
Orig. 12" now 22" W.Oak shows good scar. I do not
open, S.76½°E., 29.6 ft.
Orig. 18" now 32" B.Oak N.68°E., 46.2 ft. Shows good
scars, I do not open.
Set - Brass cap at corner mkd. S15|S14 T26S R6W County
Surveyor's Office S22|S23 1959
New BTs - 20" W.Oak bears S.72°W., 24.3 ft. scribed S22 T26S
R6W CS BT.
22" W.Oak bears S.76¾°E., 39.1 ft. scribed S23
T26S R6W CS BT.
13" W.Oak bears N.61°E., 17.8 ft. scribed S14 T26S
R6W CS BT.
13" B.Oak bears N.82°W., 45.2 ft. scribed S15 T26S
R6W CS BT.

Found OK, May 1964, M.E.G. C.S. File 52/87-9

Bruce Shaner - November 5, 1982 - C.S. File 58/229-16

(CORNER REPORT ONLY)

Found - 1" I.P. with a 2½" 1959 Co. brass cap properly mkd.
52" Oak BT snag, scribe "S" visible bears N.25½°W.,
207.4 ft. to face. (Orig. GLO rec. N.27°W.,
205.9 ft.)
32" Oak BT snag with face scars, bears N.68°E., 46.2
to face.

(Cont. Next Page)

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

22" Oak BT with healed over face, bears S.76 $\frac{3}{4}$ °E., 39.1 ft. (Orig. GLO rec. 39.6 ft.)
24" Oak BT with healed over face, bears S.69°W., 23.7 ft. (Byron rec. S.72°W., 24.3 ft.)
16" Oak BT with healed over face, bears N.61°E 17.8'
14" Oak BT with healed over face, bears N.83°W., 44.2 ft. (Byron rec. N.82°W., 45.2 ft.)
Found ok, Bruce Shaner LS# 430, Aug. 27, 1992, CS 63/138-18; 1992-0063. At fence corner: E, W, & N.
Found OK, Aug. 1995 by B. Shaner - M122-37. Found OK by Bentz, Sept. 1996 - Subd. Plat V.19 P.11 A & B
DCS0-GIS Corner visitation - 6/17/2004 - Typed: 1/27/2011 - C.S. File 67/33-1 ----- Monument - BC/IP 1.25" Comment - OK
Found Ok by Carl Sweeden, 10/2006 - M152-4 Fd. BC by D Edwards, 2/2019 - 2019-0005 Fd. BC by D Edwards, 3/2022 - 2022-0017 Fd. BC by D. Edwards 4/2026 - M186-78