

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set post, corner to Secs. 10, 11, 14 and 15, from which  
A Y.Oak 20" dia. bears S.71°E., 115 lks.  
A W.Oak 18" dia. bears N.51¼°E., 85 lks.  
A W.Oak 12" dia. bears N.61°W., 112 lks.  
A Y.Oak 18" dia. bears S.20½°W., 146 lks.

James W. Byron, Deputy - Milo Godfrey; S.A. Bilow - Feb. 11, 1959 - C.S. File 49/121-4

-----  
Found - Orig. 18" now 28" W.Oak N.51¼°E., 56.1 ft. shows good scars, I do not open.  
Orig. 12" now 19" W.Oak N.61°W., 73.9 ft. I open & find good scribing.  
Old stump holes that check bearing & distance for orig. SE and SW BTs.

Set - Brass cap at cor. mkd. S10|S11 T26S R6W  
County Surveyors Office S15|S14 1959

(sketch in file shows BC at fence intersection N & E.)

New BTs - 8" W.Oak bears East 9.7 ft. scribed S14 T26S R6W CS BT.  
11" W.Oak bears N.43½°E., 26.0 ft. scribed S11 T26S R6W CS BT.  
6" W.Oak bears S.57°W., 13.4 ft. scribed S15 T26S R6W CS BT.  
12" W.Oak bears N.44°W., 21.6 ft. scribed S10 T26S R6W CS BT.

DCS0-GIS Corner visitation - 6/16/2004 - Typed: 1/27/2011 - C.S. File 67/33-1

-----  
Monument - BC/IP 1"  
Comment - OK