

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 and 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----  
Set ¼ sec. post, from which  
    A W.Oak 8" dia. bears N.87°W., 1127 lks.  
    A W.Oak 10" dia. bears S.69½°E., 421 lks.

---

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy; Wm. Stoffel; M. Stone - July 1964 - C.S. File 52/87-65  
-----  
Found - 24" W.Oak S.69½°E., 277.9 ft. previously opened scribing visible on partially rotted face "BT".  
Did not find NW BT.  
Set - Brass cap at Cor. mkd: County Surveyors Office 1964  
          ¼     S 23  
                  S 26  
New BTs - 11" W.Oak N.44°E., 21.5 ft. mkd. ¼ S23 CS BT.  
          6" W.Oak S.5°W., 19.5 ft. mkd. ¼ S26 CS BT.  
Corner is approx. 70 ft. south of E & W fence line.

---

Found OK by Bentz, Sept. 1996 - Subd. Plat V.19 P.11 A & B