

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Corner for Secs. 2 and 11

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
 A W.Oak 15" dia. bears N.22½°W., 227 lks.
 A W.Oak 15" dia. bears S.26°E., 126 lks.

Victor McLind, for: H & D Land Co. Inc. - January, 1972
Map File M 42 - 56

No evidence of original corner, set by proportionate measurement.
Set brass cap, from which:
 12" W.Oak scribed "T26S R6W ¼ S11" bears S.79°W., 59.5 ft
 Fence corner bears S.1°E., 10.5 ft. (fences running East, West, and South.

MARK SMALLEY, JULY 1995, M 119-67 - FOR: ROSEBURG RESOURCES

FOUND - 2½" BC below ground, RLS 934 1972
BT'S FD.- 14" oak, S.79°W., 59.5' healed
 fence corner S.1°E., 10.5'
NEW BT'S- 14" cedar, S.84°E., 71.4', "¼ S BT"
 9" cedar, S.50°E., 55.3'. "¼ S BT"