TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to secs. 11,12,13 and 14, from which
A Y.Oak 13" dia. bears N.12½°W., 593 lks.
An Ash 10" dia. bears N.60¼°E., 1950 lks.
Make trench, no other trees near.

Victor McLind, for: H & D Land Co. Inc. - Jan., 1972 - M 42-56

Set by double proportionate measurement.
Set - Brass cap 6" below surface of ground in open field just East of small draw.
6" Ash scribed "T26S R6W S11 BT" bears N.23½°W., 33.0 ft
24" B.Oak scribed "T26S R6W S13 BT" bears S.48¼°E., 876.1 ft.

Douglas Co. Surveyors Office - Randall Smith; Stephen Flause
April 8, 1990 - C.S. File 64/9-3

Found - A 2½" dia. brass cap on an iron pipe flush with ground. Cap is unmarked.
6" now 13" Ash with a fully healed lower & partially healed upper blaze scribe mark visible "6" bears N.23½°W., 33.0 ft. (agrees w/record)
24" now 29" B.Oak, no blazes visible bears S.48¼°E., 876.1 ft. (agrees with record)
New BTs- 21" dia. Apple, bark scribed "T26S R6W S13 CS BT" bears S.1¾°E., 138.2 ft.
11" dia. Ash double blazed & scribed "T26S R6W S11 CS BT" bears N.1¾°W., 97.0 ft.

Fd Brass Cap - Robert Dolan, June 1993, Partition Plat 1993-0044

Fd. OK by M. Heimburger, July 1999 - M131-78