

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec Cor for 1 & 2; & 35 & 36 of T25-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to secs. 35, 36, 1 and 2, from which
A Y.Oak 10" dia. bears N.47½°E., 61 lks. dist.
A Y.Oak 15" dia. bears S.74°E., 83 lks. dist.
A Y.Oak 12" dia. bears S.81°W., 347 lks. dist.
A Laurel, 20" dia. bears N.64½°W., 344 lks. dist.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy and
Mike Stone - June & July, 1963 - C.S. File 49/123-83

Found - 16" Oak, standing but dead, S.81°W., 229.0 ft. Cut
open & found good reverse scribing "R6W T26S".
Orig. face rotted, overgrowth dead.
Portion of Oak stump S.74°E., 54.8 ft. found over-
growth of old face, badly rotted. No scribing
visible.

No trace of NW or NE bearing trees.
Set - Brass cap at cor. mkd. County Surveyors Office 1963
T25S R6W S35|S36
T26S S 2|S 1

New BTs - 13" D.Fir N.45°W., 26.2 ft. mkd. T25S R6W S35 CS BT.
8" D.Fir S.52°W., 43.8 ft. mkd. T26S R6W S2 CS BT.
10" D.Fir S.73°E., 52.4 ft. mkd. T25S R6W S1 CS BT.
16" D.Fir N.13°E., 68.3 ft. mkd. T25S R6W S36 CS BT.
A ½" Pipe and Cedar stake in E. & W. fence line bears S.29°E.,
49.8 ft.

FD. OK, MARK SMALLEY, JULY 1995, M 119-67

DCS0-GIS Corner visitation - 7/8/2004 - Typed: 01/25/2011 -
C.S. File 67/33-1

Monument - BC/IP 1.25"
Comment - ok